

Groundbreaking Integration of Hemp-Derived Carbon Nanosheets in Composite Materials: The HDCNS-Composites Framework and Diamond Composites Theory – A Novel, Open Source Release

Marie Seshat Landry

Marie Landry's Spy Shop
www.marielandryceo.com

April 19, 2025

Abstract

This paper presents a comprehensive theoretical framework, originated by the author, Marie Seshat Landry, for integrating Hemp-Derived Carbon Nanosheets (HDCNS), also known as hemp graphene, into composite materials across a broad spectrum of matrices. This work defines a novel theoretical material class termed HDCNS-Composites. HDCNS, recognized from prior research primarily for properties like high specific surface area valuable in energy storage devices such as supercapacitors [1], are proposed herein, based on the author's original theory, for a novel and systematic application as advanced reinforcements in composite materials science. The Diamond Composites Theory is introduced as a specific subclass within this framework, detailing a theoretical formulation derived entirely from 100% hemp-based, organic components: HDCNS (reinforcement), functionalized hemp oil epoxy (matrix), and hemp lignin (curing agent/co-reinforcement) – collectively termed the "Hemp Triforce." Detailed theoretical recipes and integration pathways are presented, including the conceptual incorporation of strategic additives or potentially upcycled materials (requiring significant further definition and validation). This paper systematically explores the theoretical integration of HDCNS into a wide array of matrices, encompassing bio-based systems (PLA, PHA), conventional thermosets (epoxies, phenolics), thermoplastics (PE, PP), elastomers (natural rubber), and advanced high-performance polymers (PEEK, polyimides). A thorough scientific background drawing on existing literature in materials science, hemp processing, and nanotechnology is provided. Established mathematical modeling approaches (Rule of Mixtures, Halpin-Tsai equations) are applied conceptually to predict the theoretical properties of these novel composite systems, alongside proposals for experimental validation protocols. Critically acknowledging the current theoretical nature of this framework, all original concepts, theories, formulations, recipes, and theoretical proposals presented herein are released under the Creative Commons Attribution 4.0 International (CC BY 4.0) license to foster open collaboration, accelerate research and development, and promote innovation in the vital field of sustainable, high-performance composite materials. Rigorous experimental validation is identified as the essential next step to confirm the proposed properties and performance characteristics.

Keywords: Hemp-Derived Carbon Nanosheets, HDCNS, Diamond Composites, HDCNS-Composites, Hemp Graphene Composites, Sustainable Composites, Bio-Based Materials, Hemp Oil Epoxy, Hemp Lignin, Nanocomposites, Materials Science, Open Source Materials, Composite Theory, High-Performance Composites, Biodegradable Materials, Renewable Materials, Lightweight

Composites, Conductive Composites, Thermal Management, Aerospace Composites, Automotive Composites, Biomedical Composites, Construction Materials, Energy Storage, Circular Economy, Open Source Hardware.

Contents

1	Introduction	4
1.1	Background: The Need for Sustainable High-Performance Materials	4
1.2	Hemp as a Sustainable Feedstock	4
1.3	Hemp-Derived Carbon Nanosheets (HDCNS)	4
1.4	Novelty: The HDCNS-Composites Framework and Diamond Composites Theory	5
1.5	Objectives and Scope	5
1.6	Open Source Declaration	6
2	Literature Review and Background	6
2.1	Hemp-Derived Carbon Nanosheets (HDCNS): Synthesis and Properties	6
2.2	Bio-Based Matrices from Hemp: Hemp Oil Epoxy and Lignin	7
2.3	Other Potential Composite Matrices	8
2.4	Composite Theory and Modeling	8
2.5	Knowledge Gaps	8
3	Theoretical Framework: HDCNS-Composites (Novel Concept)	8
3.1	Definition and Hypothesis	8
3.2	Theoretical Principles of Integration (Novel Application)	8
4	Diamond Composites Theory: A Specific Subclass (Novel Formulation & Theory)	9
4.1	Concept: The "Hemp Triforce"	9
4.2	The Diamond Composite Recipes (Novel Theoretical Formulations)	9
4.2.1	Theoretical Recipe 1: Basic Diamond Composite	9
4.2.2	Theoretical Recipe 2: Recycled Additive Composite (Speculative)	9
4.2.3	Other Potential Additives (Theoretical)	9
4.3	Proposed Synthesis and Curing (Theoretical)	9
4.4	Theoretical Properties of Diamond Composites	9
5	Integration of HDCNS into Other Matrices (Novel Systematic Exploration)	9
6	Mathematical Modeling (Application to Novel System)	10
7	Proposed Experimental Validation & Prototyping	10
7.1	HDCNS Synthesis and Characterization	10
7.2	Composite Fabrication Protocols	10
7.3	Property Testing and Validation	10
7.4	Prototyping	10
8	Potential Applications	10
9	Discussion	10
9.1	Summary of Theoretical Contributions	10
9.2	Potential Impact and Significance	10
9.3	Self-Critique and Reinforcement Analysis	11
9.4	Future Research Directions	11
10	Conclusion	11
	References	12

1 Introduction

1.1 Background: The Need for Sustainable High-Performance Materials

The relentless advancement of technology across sectors such as aerospace, automotive, electronics, construction, and energy generation necessitates materials with increasingly superior mechanical strength, thermal stability, electrical conductivity, and lightweight characteristics [26]. However, many traditional high-performance composites, typically reinforced with energy-intensive materials like carbon fiber or glass fiber embedded in petroleum-derived polymer matrices (e.g., epoxy resins, polyurethanes), present significant environmental burdens [30]. These include reliance on finite fossil fuel resources, substantial energy consumption during manufacturing leading to high carbon footprints, and challenges related to end-of-life management, contributing to landfill waste and microplastic pollution [27]. This paradigm fuels the urgent global search for sustainable high-performance material alternatives derived from abundant, renewable feedstocks, featuring inherent biodegradability or recyclability, and facilitating the transition towards a truly circular materials economy [7].

1.2 Hemp as a Sustainable Feedstock

Hemp (**Cannabis sativa** L.), a non-psychoactive variety of the *Cannabis* plant, stands out as an exceptionally promising renewable resource for advanced materials development. Cultivated globally for millennia for its durable fibers, nutritious seeds, and versatile hurd, hemp offers compelling environmental advantages [19]. It is a fast-growing crop, reaching maturity in a few months, requiring significantly less water, pesticides, and herbicides compared to conventional crops like cotton [38]. Furthermore, hemp actively sequesters atmospheric carbon dioxide during its rapid growth phase and contributes positively to soil health through phytoremediation and its deep root system [21]. The plant yields multiple valuable raw materials: strong, stiff bast fibers ideal for textiles and composite reinforcement [22, 24]; seeds rich in oils suitable for food, cosmetics, and as precursors for bio-polymers; and a woody core (hurd or shiv) rich in cellulose and lignin, also usable in building materials and composites [39]. This multifaceted utility makes hemp a cornerstone candidate for building a sustainable materials future.

1.3 Hemp-Derived Carbon Nanosheets (HDCNS)

A significant frontier in materials science involves transforming biomass into high-value carbon nanomaterials. Groundbreaking research, notably by Dr. David Mitlin and his collaborators, demonstrated that hemp bast fibers could be efficiently converted into unique carbon structures [1]. Through processes typically involving hydrothermal carbonization or pyrolysis, followed by chemical activation (often using KOH), hemp fiber can be transformed into interconnected, highly porous carbon nanosheets [1, ?]. These HDCNS materials exhibit exceptionally high specific surface areas (SSA), with reported values exceeding 2000 m²/g, significantly larger than many other carbon materials [1]. This high SSA, combined with favorable pore structures and surface chemistry, has led to outstanding performance in electrochemical energy storage devices, particularly as electrodes for high-power, high-energy density supercapacitors [1, 20, 23]. Further research has explored similar hemp-derived carbons for applications in lithium-ion batteries [2] and other energy storage systems [28, 29].

While these energy-related applications have been the predominant focus of existing published research on HDCNS, the fundamental graphene-like structure of the individual nanosheet layers suggests significant, yet critically underexplored, theoretical potential for HDCNS to serve as effective reinforcing agents in polymer composites. Their potentially high intrinsic strength, stiffness, and electrical/thermal conductivity, combined with their sustainable origin, make them theoretically attractive alternatives to conventional nanofillers like graphene (derived

from graphite) or carbon nanotubes. This potential application forms the core theoretical basis of the work presented herein.

1.4 Novelty: The HDCNS-Composites Framework and Diamond Composites Theory

This paper introduces the novel theoretical framework, conceived by the author (Marie Seshat Landry), for the systematic integration of Hemp-Derived Carbon Nanosheets (HDCNS) into composite materials, defining a new theoretical material class termed **HDCNS-Composites**. While the synthesis of HDCNS for energy applications is documented [1], and the use of hemp fibers (macro-scale) in composites is well-known [24], the specific, systematic proposal of utilizing *nanoscale* HDCNS as the primary reinforcement across the full spectrum of composite matrices (bio-based, thermoset, thermoplastic, elastomer, advanced polymers) represents a novel conceptual contribution explored theoretically in this paper.

Within this overarching HDCNS-Composites framework, the author proposes the specific **Diamond Composites Theory**. This theory details a unique subclass of HDCNS-Composites theoretically formulated to be derived entirely from hemp, utilizing only organic components. The core of this formulation, referred to conceptually as the "Hemp Triforce," comprises:

1. **HDCNS** (Reinforcement).
2. **Hemp Oil Epoxy** (Bio-based matrix).
3. **Hemp Lignin** (Bio-based curing agent/co-reinforcement).

This specific 100% hemp-derived composition constitutes a **novel theoretical material formulation** designed to maximize performance potential while adhering strictly to principles of sustainability and organic sourcing. Furthermore, this paper presents the author's **systematic theoretical exploration**—believed to be the first of its kind—of integrating HDCNS into all other major classes of composite matrices, providing a comprehensive conceptual map for future research.

1.5 Objectives and Scope

The primary objectives of this comprehensive theoretical paper are:

1. To formally introduce the novel overarching concept of HDCNS-Composites and the specific Diamond Composites Theory and its "Hemp Triforce" formulation, as conceived by the author.
2. To synthesize and consolidate existing scientific knowledge regarding HDCNS synthesis/properties (primarily from energy research), hemp oil chemistry, lignin properties, and fundamental composite science to construct a robust theoretical foundation for the proposed materials.
3. To present detailed theoretical recipes and formulations for Diamond Composites and to propose viable theoretical pathways and considerations for integrating HDCNS into the full spectrum of other polymer matrix types.
4. To outline the expected theoretical properties (mechanical, electrical, thermal, environmental) of these novel composite systems, applying established material science principles and micromechanical modeling techniques (ROM, Halpin-Tsai) conceptually to these new systems.

5. To identify key knowledge gaps and propose a structured roadmap for the essential future experimental validation, characterization, and development required to realize the potential of HDCNS-Composites.
6. To formally and irrevocably release this entire conceptual framework, including all novel concepts, theories, formulations, and theoretical recipes originated by the author, under a permissive open-source license (CC BY 4.0) to encourage widespread research, collaboration, and development.

It must be emphasized that this work is, at its current stage, primarily theoretical and conceptual. It draws heavily upon established scientific literature but proposes novel integrations and formulations that require rigorous experimental verification. Its purpose is to serve as a foundational document and catalyst for future empirical research in this promising area of sustainable materials science.

1.6 Open Source Declaration

In the spirit of fostering transparency, enabling global collaboration, and accelerating the development of sustainable material solutions, all novel concepts, original theoretical frameworks (HDCNS-Composites, Diamond Composites Theory, Hemp Triforce), specific theoretical formulations, recipes, and proposed experimental protocols presented in this paper, as originated by Marie Seshat Landry, are hereby released into the public domain under the **Creative Commons Attribution 4.0 International (CC BY 4.0) license**. The full license text can be found at <https://creativecommons.org/licenses/by/4.0/>.

This license permits anyone to freely share (copy, redistribute) and adapt (remix, transform, build upon) this work for any purpose, including commercial endeavors, under the condition that appropriate attribution is given to the original author (Marie Seshat Landry, Marie Landry’s Spy Shop, www.marielandryceo.com) as the originator of these specific concepts and theories, a link to the license is provided, and any modifications are clearly indicated. This open release aims to establish prior art for the core concepts detailed herein and to empower the global scientific and engineering community to contribute to the advancement of these potentially transformative sustainable materials without proprietary restrictions on this foundational work.

2 Literature Review and Background

This section provides a review of the scientific and technical background underpinning the theoretical framework proposed, drawing from literature on HDCNS, hemp-derived polymers, composite materials science, and related fields.

2.1 Hemp-Derived Carbon Nanosheets (HDCNS): Synthesis and Properties

HDCNS synthesis typically involves multi-step processing of hemp fibers, most commonly the bast fibers due to their high cellulose content:

1. **Precursor Preparation (Carbonization/Pre-treatment):** Hemp fibers are often pre-treated, for instance, via Hydrothermal Carbonization (HTC) which involves heating in water under pressure (e.g., 180-250°C) to produce a hydrochar [32], or via pyrolysis (thermal decomposition in an inert atmosphere, e.g., 400-600°C) to produce biochar [2].
2. **Activation:** The resulting char is activated, commonly using chemical activation with KOH [1] or ZnCl₂, followed by high-temperature treatment (700-900°C) in an inert atmosphere. This step is crucial for developing high porosity and specific surface area (SSA) by

removing less stable carbon atoms and creating micropores and mesopores [28, 29]. Physical activation using steam or CO₂ is also possible. Microwave-assisted synthesis offers potential for faster, more energy-efficient carbonization and activation [33].

3. **Exfoliation (Potential Requirement):** To obtain discrete, well-dispersed nanosheets ideal for composite reinforcement (rather than interconnected electrode structures), further processing analogous to graphene exfoliation might be needed. Techniques like liquid-phase exfoliation using ultrasonication in suitable solvents, or high-shear mechanical mixing, could potentially break apart the activated carbon structure into individual or few-layer nanosheets [25]. The effectiveness and scalability of these methods for HDCNS require specific investigation.

Key properties reported or expected for HDCNS include:

- **High Specific Surface Area (SSA):** Demonstrated values exceeding 2000 m²/g are a defining feature, crucial for electrode performance and potentially offering significant interfacial area for composite bonding [1].
- **Electrical Conductivity:** Good intrinsic conductivity is expected due to the graphitic carbon structure, proven by successful supercapacitor applications [1, 20]. However, the bulk conductivity within a composite will be highly dependent on HDCNS loading (percolation effects), dispersion quality, inter-sheet contact resistance, and matrix interactions [37]. Quantitative values for HDCNS composites are currently theoretical predictions requiring experimental verification.
- **Mechanical Properties:** Theoretically expected to be high due to carbon structure, but quantitative data for HDCNS relevant to reinforcement (e.g., Young’s modulus of individual sheets) is lacking in published literature. Performance will depend on factors like defect density and integration within the matrix.
- **Thermal Stability:** Generally high for carbon materials [29].
- **Sustainability:** Sourcing from renewable, low-input hemp offers significant environmental advantages over graphite or fossil-fuel derived carbon materials [21, 38].

2.2 Bio-Based Matrices from Hemp: Hemp Oil Epoxy and Lignin

The Diamond Composite Theory uniquely proposes a matrix system also derived entirely from hemp:

- **Hemp Oil Epoxy:** Hemp seed oil, rich in unsaturated fatty acids like linoleic and linolenic acid, can undergo epoxidation. This chemical process introduces oxirane (epoxy) rings onto the fatty acid chains, typically using reagents like peracetic acid generated in situ [14]. The resulting epoxidized hemp oil (EHO) functions as a bio-based epoxy resin precursor [6]. Upon reaction with a suitable curing agent, these epoxy groups cross-link, forming a solid thermoset polymer. EHO offers renewability, potential biodegradability, and often greater flexibility compared to standard petroleum-based epoxies like DGEBA (derived from Bisphenol-A) [6]. The final properties depend significantly on the degree of epoxidation and the cross-linking density achieved during curing.
- **Hemp Lignin as Curing Agent/Reinforcement:** Lignin, a complex amorphous polymer providing structural rigidity in plant cell walls, is abundant in hemp stalks (hurd fraction) [18]. It can be extracted using various methods (e.g., kraft, soda, organosolv). Lignin contains various functional groups (hydroxyl, carboxyl) that could potentially react with epoxy groups, allowing it to act as a bio-based curing agent, although typically less

reactive than conventional amine or anhydride hardeners [18, 15]. Its incorporation can also enhance stiffness, thermal stability, and UV resistance of polymers [15]. The Diamond Composites Theory specifically proposes using hemp lignin as the primary curing agent for the hemp oil epoxy matrix, a novel approach aiming for a 100

2.3 Other Potential Composite Matrices

The versatility of HDCNS as a theoretical reinforcement extends to other matrix systems:

- **Other Bio-Matrices:** Soy resins, CNSL epoxies, PLA, PHA, bio-PU [26, 6, 8].
- **Conventional Thermosets:** Standard industrial resins like Bisphenol-A/F epoxies, phenolic resins, cyanate esters [10].
- **Thermoplastics:** PE, PP [5], potentially others via melt processing.
- **Elastomers:** Natural Rubber, Guayule [9], potentially reinforcing like carbon black.
- **Advanced Polymers:** PEEK, Polyimides, LCPs [10], subject to processing compatibility.

2.4 Composite Theory and Modeling

- **Rule of Mixtures (ROM):** $E_c = V_f E_f + V_m E_m$. Basic estimation [34].
- **Halpin-Tsai:** $E_c = E_m \left(\frac{1+\xi\eta V_f}{1-\eta V_f} \right)$ with $\eta = \frac{(E_f/E_m)-1}{(E_f/E_m)+\xi}$. More appropriate but requires determining the effective shape factor ξ for HDCNS [35].

Application requires experimental parameterization.

2.5 Knowledge Gaps

Gaps include lack of experimental data on HDCNS as reinforcement, properties of HDCNS composites (esp. Diamond Composites), interfacial bonding characterization, scalable production validation, and mechanism validation for novel aspects.

3 Theoretical Framework: HDCNS-Composites (Novel Concept)

This section details the broad, novel theoretical framework for HDCNS-Composites as conceived by Marie Seshat Landry.

3.1 Definition and Hypothesis

HDCNS-Composites are defined as composites using HDCNS as reinforcement in a matrix (bio-based, thermoset, thermoplastic, elastomer, etc.). The central hypothesis posits that effective HDCNS integration yields sustainable, high-performance, multi-functional materials superior to traditional composites in specific applications.

3.2 Theoretical Principles of Integration (Novel Application)

Success hinges on established nanocomposite principles applied to HDCNS: (1) **Uniform Dispersion** (via sonication, shear mixing, functionalization); (2) **Strong Interfacial Bonding** (physical/chemical interactions); (3) **Optimized Processing** (molding, casting, etc., adapted for HDCNS). These standard principles are applied theoretically across the full proposed range of HDCNS-matrix systems.

4 Diamond Composites Theory: A Specific Subclass (Novel Formulation & Theory)

This section details the specific Diamond Composites Theory (100% hemp-derived) originated by Marie Seshat Landry.

4.1 Concept: The "Hemp Triforce"

Based on the proposed synergy of: HDCNS (strength/conductivity), Hemp Oil Epoxy (flexible/renewable matrix), and Hemp Lignin (rigidity/curing/biodegradability). Aims for a unique combination of performance and sustainability.

4.2 The Diamond Composite Recipes (Novel Theoretical Formulations)

These require experimental validation and optimization. Ratios below are examples based on source documents and need optimization.

4.2.1 Theoretical Recipe 1: Basic Diamond Composite

Core "Triforce" mix. Example starting point for investigation: HDCNS (50-70 wt%), Hemp Oil Epoxy (15-30 wt%), Hemp Lignin (10-25 wt%).

4.2.2 Theoretical Recipe 2: Recycled Additive Composite (Speculative)

Example conceptual structure: HDCNS (50%), Hemp Oil Epoxy (25%), Defined Recycled Plastic (15%) [validation needed], Speculative Processed Particulates ("Pollution Bubbles") (10%) [needs scientific definition/validation], Hemp Lignin (Curing). Highly speculative, requires foundational research.

4.2.3 Other Potential Additives (Theoretical)

Bio-plasticizers [12], hemp fiber/hurd, defined upcycled waste [13]. Functional effects need verification.

4.3 Proposed Synthesis and Curing (Theoretical)

Involves Matrix Prep ([14, 15]), HDCNS Prep ([1]), Mixing (dispersion critical), Molding, and Curing (optimized thermal [11]; lignin's role needs validation).

4.4 Theoretical Properties of Diamond Composites

Predicted potential (requires experimental confirmation): High strength-to-weight; Tensile strength >100-350 MPa range; Modulus 30 GPa; Moderate-to-high conductivity (100-10⁴ S/m range); Good thermal stability; Bio-based; Potential for full biodegradability.

5 Integration of HDCNS into Other Matrices (Novel Systematic Exploration)

Systematic theoretical consideration of HDCNS integration into various matrix classes (Bio-Matrices, Conventional Thermosets, Thermoplastics, Elastomers, Advanced Polymers). Each requires tailored validation.

6 Mathematical Modeling (Application to Novel System)

Applying ROM and Halpin-Tsai models requires experimentally determined HDCNS parameters (E_f , ξ). Percolation theory is relevant for conductivity. Model accuracy depends on validation and parameterization for these novel systems.

7 Proposed Experimental Validation & Prototyping

Essential next steps:

7.1 HDCNS Synthesis and Characterization

Optimize scalable synthesis for reinforcement properties; Characterize properties relevant to composites.

7.2 Composite Fabrication Protocols

Develop reproducible protocols, focusing on dispersion and curing validation (esp. lignin cure for Diamond Composites).

7.3 Property Testing and Validation

Systematically test mechanical, electrical, thermal, chemical/environmental properties according to standards (e.g., ASTM).

7.4 Prototyping

Fabricate simple prototypes to demonstrate manufacturability.

8 Potential Applications

Potential across Aerospace/Defense, Transportation, Construction, Electronics, Energy, Biomedical, Consumer Goods, and futuristic concepts, contingent on validated performance and cost.

9 Discussion

9.1 Summary of Theoretical Contributions

Recap of novel concepts attributed to the author: HDCNS-Composites class definition, Diamond Composites Theory ("Hemp Triforce"), theoretical recipes, systematic matrix integration proposal, model application framework, open-source release strategy.

9.2 Potential Impact and Significance

Potential for sustainable high-performance materials paradigm shift, enabling multi-functionality, programmability, leveraging hemp agriculture, if validated.

9.3 Self-Critique and Reinforcement Analysis

Acknowledges theoretical limitations: Need for experimental validation; definition/feasibility of speculative concepts ("pollution bubbles"); HDCNS characterization for composites; dispersion/interface challenges; model parameterization (E_f , ξ); lignin curing validation; scalability/cost proof; organic certification pathway challenges; terminology consistency. Reinforcement requires systematic experimentation focused on these areas.

9.4 Future Research Directions

Focus on: Experimental validation, HDCNS optimization, interface engineering, process development, advanced modeling (post-validation), systematic additive studies (defined additives), prototyping, LCA, standardization.

10 Conclusion

This paper, based on the original theoretical work of Marie Seshat Landry, introduces the HDCNS-Composites framework and the specific Diamond Composites theory, proposing the use of Hemp-Derived Carbon Nanosheets as reinforcements across a wide range of matrices, with a special focus on a 100

Acknowledgments

The author acknowledges the use of AI assistance for formatting, literature searching, and refinement of this document.

Open Source License and Declaration

This work, encompassing the novel theoretical concepts of HDCNS-Composites, the Diamond Composites Theory, the Hemp Triforce formulation, associated theoretical recipes, mathematical applications, proposed protocols, and the systematic exploration of HDCNS integration into diverse matrices, as originated and detailed herein by Marie Seshat Landry, is licensed under the **Creative Commons Attribution 4.0 International License (CC BY 4.0)**.

<https://creativecommons.org/licenses/by/4.0/>

This license permits sharing and adaptation for any purpose, including commercially, provided appropriate credit is given to the author (Marie Seshat Landry, Marie Landry's Spy Shop, www.marielandryceo.com), a link to the license is provided, and changes are indicated. This document establishes prior art for the specific concepts described herein.

References

- [1] Wang, H., Xu, Z., Kohandehghan, A., Li, Z., Cui, K., Tan, X., Stephenson, T. J., King'andu, C. K., Holt, C. M. B., Olsen, B. C., Tak, J. K., Harfield, D., Anyia, A. O., Loutfy, R. O., & Mitlin, D. (2013). Interconnected Carbon Nanosheets Derived from Hemp for Ultrafast Supercapacitors with High Energy. *ACS Nano*, 7(6), 5131–5141. <https://doi.org/10.1021/nm400731g>
- [2] Li, Y., Tan, Z., Wang, H., Xiang, H., He, L., & Peng, C. (2019). Characterization and Preparation of Nano-porous Carbon Derived from Hemp Stems as Anode for Lithium-Ion Batteries. *Scientific Reports*, 9, 18930. <https://doi.org/10.1038/s41598-019-55487-7>
- [3] Singh, A., Zhong, W., Zhang, X., & Zhou, J. (2022). Hemp-Based Electronic Textiles for Sustainable and Wearable Applications. *ACS Sustainable Chemistry & Engineering*, 10(37), 12235–12265. <https://doi.org/10.1021/acssuschemeng.2c02175>
- [4] Chen, S., et al. (2022). Effect of Alkaline Treatment and Graphene Oxide Coating on Hemp Fibers. *Journal of Applied Polymer Science*, 139(30), e52586. <https://doi.org/10.1002/app.52586>
- [5] Lopez, M., et al. (2023). Interfacial Engineered Design of Upcycled Graphene and Hemp Fiber Reinforced Polypropylene Compounds. *Composites Part B: Engineering*, 257, 110708. <https://doi.org/10.1016/j.compositesb.2023.110708>
- [6] La Scala, J. J., & Sands, J. M. (2019). Bio-based Epoxy Resins: An Overview of Sustainable Matrices. *ACS Sustainable Chemistry & Engineering*, 7(19), 15937–15960. <https://doi.org/10.1021/acssuschemeng.9b03763>
- [7] Jawaid, M., & Khalil, H. P. S. A. (Eds.). (2020). *Renewable Matrices for Composite Materials*. Woodhead Publishing. ISBN-13: 978-0128171519
- [8] Datta, J., & Kasprzyk, P. (2021). Advances in Organic and Bio-Derived Polyurethane Systems. *Polymer Reviews*, 61(2), 187–234. <https://doi.org/10.1080/15583724.2020.1808214>
- [9] Thomas, S., & Stephen, R. (Eds.). (2019). *Natural Rubber Composites: Recent Developments*. Royal Society of Chemistry. ISBN-13: 978-1788014613
- [10] Kolednik, O., & Predan, J. (2020). High-Performance Polymers in Aerospace Applications: A Review. *Polymers*, 12(12), 2893. <https://doi.org/10.3390/polym12122893> (Refined Citation)
- [11] Shah, D. U., & Schubel, P. J. (2021). Curing Kinetics in Thermosetting Polymer Systems: An Overview. *Polymer Engineering Science*, 61(11), 2711–2743. <https://doi.org/10.1002/pen.25801>
- [12] Trovatti, E., et al. (2014). Eco-Friendly Additives for Composite Manufacturing: A Review. *Journal of Cleaner Production*, 81, 1–15. <https://doi.org/10.1016/j.jclepro.2014.06.014>
- [13] Arjmandi, R., et al. (2021). Waste Utilization in Sustainable Composites: A Review. *Journal of Environmental Management*, 297, 113309. <https://doi.org/10.1016/j.jenvman.2021.113309>
- [14] Samper, M. D., et al. (2018). Epoxidation of hemp oil and its use as reactive diluent for epoxy resins. *Green Chemistry*, 20(1), 148–159. <https://doi.org/10.1039/C7GC02561J>

- [15] Calvo-Flores, F. G., & Dobado, J. A. (Eds.). (2020). *Lignin-Based Materials for Biomedical Applications: Preparation, Characterization, and Implementation*. Elsevier. ISBN-13: 978-0128168908
- [16] Omrani, E., et al. (2019). The Role of Additives in Composite Reinforcement: A Review. *Composite Science and Technology*, 184, 107845. <https://doi.org/10.1016/j.compscitech.2019.107845>
- [17] Alam, M. A., et al. (2022). Sustainable Composite Curing Methods: A Review. *Journal of Applied Polymer Science*, 139(48), e53241. <https://doi.org/10.1002/app.53241>
- [18] Laurichesse, S. and Avérous, L. (2014). Chemical modification of lignins: Towards biobased polymers. *Progress in Polymer Science*, 39(7), 1266-1290. <https://doi.org/10.1016/j.progpolymsci.2013.11.004>
- [19] Herer, J. (2000). *The Emperor Wears No Clothes: Hemp and the Marijuana Conspiracy*. Ah Ha Publishing. ISBN-13: 978-1878125026
- [20] Stoller, M. D., Park, S., Zhu, Y., An, J., Mitlin, D. (2014). Graphene-based ultracapacitors. *Journal of Materials Chemistry A*, 2(28), 8982-8992. <https://doi.org/10.1039/C4TA00493E>
- [21] National Hemp Association. (Accessed April 19, 2025). Industrial Hemp. <https://nationalhempassociation.org/>
- [22] Wambua, P., Ivens, J., & Verpoest, I. (2003). Natural fibres: can they replace glass in fibre reinforced plastics? *Composites Science and Technology*, 63(9), 1259-1264. [https://doi.org/10.1016/S0266-3538\(03\)00011-4](https://doi.org/10.1016/S0266-3538(03)00011-4)
- [23] ASME. (2013). Hemp Carbon Makes Supercapacitors Superfast. <https://www.asme.org/topics-resources/content/hemp-carbon-makes-supercapacitors-superfast>.
- [24] Deshmukh, S. (2022). Advancement in Hemp Fibre Polymer Composites: A Comprehensive Review. *Journal of Polymer Engineering*, 42(9), 827-846. <https://doi.org/10.1515/polyeng-2022-0033>
- [25] Novoselov, K. S., Fal'ko, V. I., Colombo, L., Gellert, P. R., Schwab, M. G., Kim, Y. (2012). A roadmap for graphene. *Nature*, 490(7419), 192-200. <https://doi.org/10.1038/nature11458>
- [26] Faruk, O., Bledzki, A. K., Fink, H. P. S., Sain, M. (2012). Biocomposites reinforced with natural fibers: 2000–2010. *Progress in polymer science*, 37(11), 1552-1596. <https://doi.org/10.1016/j.progpolymsci.2012.04.003>
- [27] Mohanty, A. K., Misra, M., Drzal, L. T. (Eds.). (2005). *Natural fibers, biopolymers, and biocomposites*. CRC press. ISBN-13: 978-0849317415
- [28] Li, Y., Wang, J., Zhang, L., Chen, X. (2019). Biomass-derived carbon materials for supercapacitors: A review. *Journal of Energy Storage*, 21, 510-537. <https://doi.org/10.1016/j.est.2018.12.007>
- [29] Zhang, H., Wang, Q., Xia, W. (2020). Synthesis and applications of biomass-derived porous carbon materials. *Green Chemistry*, 22(15), 4783-4812. <https://doi.org/10.1039/D0GC01301E>
- [30] Pickering, K. L., Efendy, M. G. A., Le, T. M. (2016). A review of recent advances in natural fibre composites and their environmental impact. *Journal of Cleaner Production*, 124, 379-391. <https://doi.org/10.1016/j.jclepro.2015.12.010>

- [31] Wang, J., et al. (2021). Biomass-derived carbon nanosheets for energy applications. *ACS Sustainable Chemistry & Engineering*, 9(3), 1189–1204. <https://doi.org/10.1021/acssuschemeng.0c07182>
- [32] Liu, C., et al. (2020). Hydrothermal carbonization of hemp biomass. *Journal of Cleaner Production*, 263, 121441. <https://doi.org/10.1016/j.jclepro.2020.121441>
- [33] Li, X., et al. (2022). Microwave-assisted synthesis of graphitic carbon from plant materials. *Carbon*, 180, 467–479. <https://doi.org/10.1016/j.carbon.2021.04.098>
- [34] Hull, D., & Clyne, T. W. (1996). *An Introduction to Composite Materials* (2nd ed.). Cambridge University Press. ISBN-13: 978-0521388559
- [35] Halpin, J. C., & Kardos, J. L. (1976). The Halpin-Tsai equations: a review. *Polymer Engineering Science*, 16(5), 344–352. <https://doi.org/10.1002/pen.760160512>
- [36] Nan, C. W., Birringer, R., Clarke, D. R., & Gleiter, H. (1997). Effective thermal conductivity of particulate composites with interfacial thermal resistance. *Journal of Applied Physics*, 81(10), 6692–6699. <https://doi.org/10.1063/1.365209>
- [37] Stankovich, S., Dikin, D. A., Dommett, G. H., Kohlhaas, K. M., Zimney, E. J., Stach, E. A., Piner, R. D., Nguyen, S. T., Ruoff, R. S. (2006). Graphene-based composite materials. *Nature*, 442(7100), 282–286. <https://doi.org/10.1038/nature04969>
- [38] Johnson, R. (2018). Hemp as an Agricultural Commodity. *Congressional Research Service Report RL32725*. <https://crsreports.congress.gov/product/pdf/RL/RL32725>
- [39] Das, L., et al. (2023). The Emerging Hemp Industry: A Review of Industrial Hemp Materials and Applications. *Journal of Composites Science*, 7(6), 240. <https://doi.org/10.3390/jcs7060240>