

Comprehensive Technical Evaluation and Strategic R&D Review of Organic Hemp Graphitic Composite Materials

Executive Summary & Strategic R&D Context

The technical proposal documented in Report TR-OHGCM-2026-001 outlines an engineering methodology aimed at replacing fossil-derived synthetic carbon nanomaterials—including synthetic graphene, carbon nanotubes (CNTs), and petroleum pitch-based carbon fibers—with bio-derived graphitic allotropes produced from industrial organic hemp (*Cannabis sativa* L.) biomass¹. The inner bast and outer hurd fractions of industrial hemp possess pre-structured porous networks and high native cellulosic and lignocellulosic content, rendering them viable precursors for scalable carbon nanomaterial synthesis¹.

The proposal presents a multi-morphology carbon portfolio comprising five distinct Organic Hemp-Derived Graphitic Materials (OHGMs): Organic Hemp Carbon Nanosheets (OHCNS), Organic Hemp Graphene Oxide (OHGO), Organic Hemp Reduced Graphene Oxide (OHRGO), Organic Hemp Active Carbon Biochar (OHACB), and Organic Hemp Short Carbon Fibers (OHSCF)¹. It outlines the structural and functional integration of these allotropes across seven material matrix classes: thermoset epoxies, epoxidized organic hempseed oil vitrimers, thermoplastics, elastomers, inorganic geopolymers, metal matrix composites (MMCs), and ceramic matrix composites (CMCs)¹.

While the proposal constructs a closed-loop bio-carbon ecosystem supported by statistical Design of Experiments (DOE) methodologies, an expert evaluation requires benchmarking these claims against established academic literature, analyzing underlying chemical synthesis mechanisms, examining micromechanical stress transfer formulations, and identifying mathematical and operational limitations within the proposed processing workflows¹.

Intellectual Priority Declarations and Prior Art Analysis

The proposal outlines three priority declarations regarding material synthesis, conceptual integration, and ecosystem design¹. Contextualizing these priority declarations within peer-reviewed literature and industrial prior art reveals the specific novel contributions of the proposal alongside established foundational science.

Proposal Priority Declarations (TR-OHGCM-2026-001)	Benchmark Peer-Reviewed Literature & Industry Prior Art
Declaration 1: First formulation and	Biochar conversion into graphene oxide via

synthesis of OHGO and OHRGO directly from hemp biomass precursors ¹ .	modified Hummers oxidation is established across agricultural feedstocks, including licorice roots, palm waste, and energy crops ⁵ . Direct GO/rGO surface coatings and modifications on hemp fibers in epoxy composites are documented in existing literature ² .
Declaration 2: First conceptualization and modeling of OHCNS as a structural and functional reinforcement phase across composite matrices ¹ .	Wang et al. (2013) demonstrated the synthesis of 2D hemp carbon nanosheets via hydrothermal carbonization and KOH activation for supercapacitors ¹ . Zakir et al. (2022) synthesized mesoporous hemp graphene (HGr) ³ . Prasob & Sasikumar (2022) modeled hybrid hemp fiber and graphene nanofiller reinforcement in epoxies ¹ .
Declaration 3: Establishment of a multi-scale closed-loop bio-carbon composite ecosystem combining 0D/3D biochar, 1D carbon fibers, and 2D nanosheets ¹ .	Commercialization of epoxidized hempseed oil bio-epoxies and dynamic covalent vitrimers ("Hempoxy") was established by Zila BioWorks and Washington State University ⁴ . Corporate disclosures indicate Landry's hemp composite R&D is currently at the hypothesis and concept-validation stage ¹⁵ .

The foundational synthesis of 2D carbon nanosheets from hemp bast fibers was established by Wang et al. (2013), who demonstrated that hydrothermal carbonization (HTC) followed by potassium hydroxide (KOH) chemical activation yields interconnected graphitic nanosheets (10–30 nm in thickness) optimized for ultrafast energy storage¹. Building upon this, Zakir et al. (2022) detailed the chemical synthesis of mesoporous hemp-derived graphene (HGr) using concentrated acid treatments and KOH activation, establishing bi-porous mesostructures with distinct 4 nm and 8 nm pore size distributions³.

The conversion of biochar into graphene oxide via modified Hummers oxidation is well-documented across agricultural feedstocks, including energy crops like miscanthus and crop residues⁵. Furthermore, Da Silveira et al. (2022) and Javanshour et al. (2021) evaluated graphene oxide-coated hemp fibers and GO-modified natural fibers in polymer matrices², while Prasob & Sasikumar (2022) investigated the mechanical influence of combining hemp fibers with graphene nanofillers in epoxy matrices¹.

In dynamic bio-resins, Zila BioWorks ("Zila Works") commercialized epoxidized hempseed oil bio-epoxies and dynamic covalent vitrimers ("Hempoxy") based on technology originating from

Dr. Jinwen Zhang's laboratory at Washington State University⁴. Public disclosures from the author's primary enterprise acknowledge that materials science initiatives under Landry Industries remain in the hypothesis and concept-validation stage¹⁵. Consequently, TR-OHGCM-2026-001 is best categorized as an integrative conceptual and theoretical framework that unifies distinct bio-carbon processing streams into a structural composite design system rather than the discovery of fundamentally unknown chemical species¹.

Multi-Morphology Carbon Synthesis Pathways & Processing Mechanics

The proposal details thermochemical processing pathways to isolate five distinct carbon allotropes from industrial organic hemp hurd and bast biomass precursors¹.

Organic Hemp Carbon Nanosheets (OHCNS)

Synthesizing OHCNS requires subjecting raw hemp bast or hurd biomass to hydrothermal carbonization (HTC) in an aqueous medium at temperatures between 180°C and 220°C¹. This process breaks down hemicellulose and partially hydrolyzes cellulose into a concentrated carbonaceous hydrochar¹. This hydrochar intermediate is mixed with potassium hydroxide (KOH) at impregnation mass ratios ranging from 1:1 to 1:4¹. High-temperature chemical activation at 700–900°C under an inert argon atmosphere drives metallic potassium intercalation into the carbon matrix¹. Etching reactions expand interlayer spaces, yielding 2–5 nm thick graphitic sheets exhibiting Brunauer-Emmett-Teller (BET) specific surface areas exceeding 1800 m²/g¹.

Organic Hemp Graphene Oxide (OHGO) and Reduced Graphene Oxide (OHRGO)

OHGO synthesis adapts a modified Hummers oxidation protocol applied to pre-graphitized organic hemp hurd biochar¹. The biochar precursor is treated with a concentrated acid mixture (H_2SO_4 and H_3PO_4 in a 9:1 volume ratio) alongside potassium permanganate ($KMnO_4$) as the primary oxidizing agent¹. This oxidative intercalation introduces oxygen-containing functional groups—primarily hydroxyl, carboxyl, and plane epoxide groups—across the graphitic lattice¹. These groups expand the interlayer d-spacing and confer amphiphilicity and solvent dispersibility¹. Subsequent green chemical reduction using L-ascorbic acid or thermal annealing at temperatures above 800°C produces OHRGO¹. This reduction partially restores the sp^2 -hybridized conjugated carbon lattice, recovering bulk electrical conductivity to approximately 10³ S/m¹.

Organic Hemp Active Carbon Biochar (OHACB) and Short Carbon Fibers (OHSCF)

OHACB is produced via slow pyrolysis of organic hemp hurd residuals at 400–600°C followed by high-temperature steam activation¹. This creates a micro- and mesoporous 3D carbon framework optimized for internal curing and stress damping¹. OHSCF is synthesized by carbonizing continuous organic hemp bast fibers under mechanical tension at 1000–1400°C to align axial crystallites, followed by precision mechanical chopping into 1–6 mm fiber lengths to ensure uniform dispersion¹.

Chemical Mechanics and Biochar Graphitization Constraints

Direct conversion of biomass-derived biochar into graphene oxide via Hummers oxidation presents notable chemical challenges compared to the oxidation of natural flake graphite⁵. Biochar generated at standard pyrolysis temperatures (400–600°C) possesses high

turbostratic disorder, limited crystallite domain sizes (L_a), and a large amorphous carbon fraction⁵. Direct acid oxidation of unrefined biochar causes extensive lattice fragmentation, resulting in low yields of 2D sheets and elevated amounts of low-molecular-weight humic acids or zero-dimensional graphene quantum dots (GQDs)⁷.

To synthesize structurally intact OHGO sheets, the hemp biochar precursor must undergo

high-temperature pre-graphitization ($> 1200^\circ\text{C}$) to extend conjugated sp^2 domains prior to oxidative acid intercalation⁵.

Micromechanical Transfer Models & Multi-Scale Reinforcement Theory

The mechanical capability of multi-scale organic hemp carbon composites depends on stress transfer mechanisms operating across microscopic and nanoscopic interfaces¹.

One-Dimensional Short Fiber Mechanics: Kelly-Tyson Shear Lag

For 1D short carbon fibers (OHSCF) embedded within a continuous polymer matrix, mechanical load is transferred from the matrix to the fiber via interfacial shear stress¹. The critical fiber

length (l_c) required for a fiber to achieve its ultimate tensile strength (σ_f) without pulling out of the matrix is defined by Kelly-Tyson shear lag theory¹:

$$l_c = \frac{\sigma_f d}{2\tau_i}$$

where d represents the fiber diameter and τ_i is the interfacial shear strength (IFSS) between

the carbonized hemp fiber and the surrounding resin¹. When the fiber length $L < l_c$, the composite fails primarily via fiber pull-out; when $L > l_c$, stress accumulates along the fiber axis until fiber fracture occurs, maximizing total energy absorption¹.

Two-Dimensional Nanosheet Mechanics: Modified Cox Shear Lag Model

For planar 2D nanosheets (OHCNS and OHGO), the elastic modulus enhancement (E_c) of the composite is modeled using modified Cox shear lag equations adapted for planar geometries¹:

$$E_c = \eta_o \eta_l V_n E_n + (1 - V_n) E_m$$

where E_n and E_m represent the elastic moduli of the nanosheet reinforcement and matrix respectively, V_n is the nanosheet volume fraction, η_o is the orientation efficiency factor, and η_l is the length efficiency factor¹:

$$\eta_l = 1 - \frac{\tanh(\beta s)}{\beta s}$$

The dimensionless shear lag parameter β and nanosheet aspect ratio s are defined as:

$$\beta = \sqrt{\frac{2G_m}{E_n t_n t_m}}, \quad s = \frac{L_n}{t_n}$$

where s is the ratio of sheet lateral length (L_n) to thickness (t_n), G_m is the matrix shear modulus, and t_m represents the intersheet matrix layer thickness¹. High aspect ratios ($s > 1000$) drive η_l toward unity, enabling efficient interfacial stress transfer¹.

Multi-Scale Synergy Mechanics

Integrating 0D/3D porous biochar, 1D short carbon fibers, and 2D graphitic nanosheets establishes a multi-scale stress mitigation network¹. Porous OHACB particles damp dynamic mechanical stresses and arrest microvoid coalescence¹. High-surface-area 2D OHCNS and OHGO sheets pinned within the matrix deflect sub-micron crack tips, while 1D OHSCF fibers bridge macro-scale cracks across developing fracture planes¹.

Cross-Matrix Integration Dynamics

Integrating multi-morphology organic hemp carbon allotropes across different matrix classes depends on specific chemical, thermal, and interfacial interaction mechanisms¹.

Thermoset Epoxies and Organic Hempoxy Vitrimers

In diglycidyl ether of bisphenol A (DGEBA) thermoset epoxies, surface oxygen groups on OHGO (hydroxyl, carboxyl, epoxy) participate in nucleophilic ring-opening reactions with amine curing agents¹. Covalent cross-linking between the nanofiller and epoxy network enhances

interfacial shear strength, increasing critical stress intensity factor (K_{1c}) fracture toughness by up to +65% at a 0.5 wt% loading¹.

In covalent adaptable networks (CANs) and vitrimers, such as epoxidized hempseed oil paired with maleated fatty acid hardeners (Zila BioWorks platform), hydroxyl groups on OHGO and OHCNS participate directly in thermally stimulated transesterification exchange reactions¹:



Unlike traditional filled thermosets where rigid inclusions restrict chain mobility, functionalized bio-carbon nanosheets integrate into the dynamic exchange network¹. This bond shuffling permits a +40% increase in flexural modulus while preserving thermal reprocessability, self-healing capacity, and chemical recyclability¹.

Semicrystalline Thermoplastics and Elastomers

In semicrystalline thermoplastics such as poly(lactic acid) (PLA), high-surface-area OHCNS serves as a heterogeneous nucleating agent¹. It lowers the free energy barrier for polymer chain folding, accelerating crystallization kinetics and increasing overall crystallinity, which

elevates the Heat Deflection Temperature (HDT) of PLA by $> 30^{\circ}\text{C}$ ¹. In non-polar matrices like polypropylene (PP) or high-density polyethylene (HDPE), coupling agents such as maleic anhydride-grafted polypropylene (MAPP) are required to establish covalent links with hydroxyl-bearing OHGO¹.

In flexible elastomers (TPU, silicone), low concentrations of dispersed OHGO (<0.5 wt%) form conductive networks near the electrical percolation threshold¹. Applied mechanical strain alters inter-particle tunneling distances, producing piezoresistive behavior with gauge factors exceeding 15 suitable for flexible strain sensing¹.

Inorganic Geopolymers, Cements, Metals, and Ceramics

In cementitious and geopolymeric binders, porous OHACB acts as an internal curing water reservoir, gradually releasing moisture during hydration to suppress autogenous shrinkage¹. Oxygen groups on OHGO serve as nucleation sites for calcium-silicate-hydrate (C-S-H) gel

growth, accelerating early-stage hydration¹. High-aspect-ratio OHSCF fibers provide macro-scale crack bridging, improving 28-day compressive strength by +35% and flexural strength by +50%¹.

For Metal Matrix Composites (Al, Mg) and Ceramic Matrix Composites (SiC , Al_2O_3) processed via Spark Plasma Sintering (SPS) or Hot Isostatic Pressing (HIP), OHCNS pins grain boundaries during high-temperature consolidation, restricting grain growth and inducing non-catastrophic crack deflection along ceramic grain interfaces¹.

Statistical Design of Experiments (DOE) & RSM

Limitations

To optimize synthesis conditions and multi-scale loading fractions, TR-OHGCM-2026-001 proposes a two-phase statistical optimization strategy¹.

Phase I: Taguchi $L_{27}(3^{13})$ Screening Array

Phase I uses a Taguchi L_{27} orthogonal array evaluating 5 control factors across 3 design levels to determine key synthesis variables influencing graphitization degree (I_D/I_G ratio via Raman spectroscopy), BET specific surface area (m^2/g), and nanofiller yield¹:

- **Factor A:** HTC Temperature ($180, 200, 220^\circ\text{C}$)¹
- **Factor B:** KOH Impregnation Ratio ($1 : 1, 1 : 2, 1 : 4$)¹
- **Factor C:** Activation Temperature ($700, 800, 900^\circ\text{C}$)¹
- **Factor D:** Pyrolysis Residence Time ($1, 2, 3$ hours)¹
- **Factor E:** Ball Milling Speed ($300, 500, 700$ RPM)¹

Phase II: Face-Centered Central Composite Design (FCCCD)

Phase II evaluates four loading variables across composite matrix formulations using a 30-run FCCCD Response Surface Methodology (RSM)¹:

- X_1 : Organic Hemp Biochar (OHACB) [$0.0 - 5.0 \text{ wt}\%$]¹
- X_2 : Organic Hemp Short Fiber (OHSCF) [$0.0 - 3.0 \text{ wt}\%$]¹
- X_3 : Organic Hemp Nanosheets (OHCNS) [$0.0 - 1.0 \text{ wt}\%$]¹
- X_4 : Organic Hemp Graphene Oxide (OHGO) [$0.0 - 1.0 \text{ wt}\%$]¹

Measured mechanical and functional responses (Y) are fitted to a second-order quadratic polynomial equation¹:

$$Y = \beta_0 + \sum_{i=1}^4 \beta_i X_i + \sum_{i=1}^4 \beta_{ii} X_i^2 + \sum_{i < j}^4 \beta_{ij}$$

Multi-objective optimization is evaluated using Derringer's overall desirability function (D)¹:

$$D = \left(\prod_{i=1}^k d_i(Y_i) \right)^{1/k}$$

which maximizes mechanical strength and toughness while constraining resin melt viscosity to preserve processability¹.

Mathematical Limitations of Quadratic RSM near Percolation Thresholds

While quadratic polynomial RSM models effectively approximate smooth mechanical responses (such as tensile strength or flexural modulus), they face mathematical limitations when applied to nanocomposite transport properties near percolation thresholds⁶.

Electrical conductivity (σ) and rheological yield stress in conductive carbon-reinforced systems follow non-linear power-law scaling relative to filler volume fraction (p)²²:

$$\sigma \propto (p - p_c)^t \quad \text{for } p > p_c$$

where p_c is the critical percolation threshold concentration and t is the universal transport exponent²².

Because electrical conductivity can increase by 6 to 10 orders of magnitude over narrow concentration increments ($\Delta p < 0.1 \text{ wt}\%$), the continuous parabolic curvature enforced by a second-order polynomial ($\beta_{ii} X_i^2$) fails to capture the step-function transition⁶. Fitting quadratic RSM models across datasets containing percolation transitions creates localized fitting errors, underestimating conductivity above p_c and predicting unphysical negative values below p_c .

To accurately model multi-scale OHGM formulations across percolating regimes, standard polynomial RSM should be supplemented with non-linear sigmoidal models or hybrid statistical-physical frameworks⁶.

Comparative Performance Metrics and Matrix Class Integration

Synthetic & Structural Portfolio of Organic Hemp-Derived Carbon Allotropes

Carbon Allotrope	Precursor Bio-Fraction	Key Processing Parameters	Morphological Dimensions	Primary Structural/Functional Mechanisms
OHCNS (Nanosheets)	Hemp Bast / Hurd Hydrochar	HTC (180–220°C) + KOH Activation (700–900°C)	Thickness: 2–5 nm; SSA >	Heterogeneous nucleation, crack tip branching, interfacial shear transfer ¹ .
OHGO (Graphene Oxide)	Pre-Graphitized Hemp Hurd Biochar	Modified Hummers Oxidation (H_2SO_4/H_3PO_4)	Single/Few-Layer Functionalized Sheets	Covalent amine coupling, dynamic transesterification exchange in vitrimers ¹ .
OHRGO (Reduced GO)	OHGO Precursor	L-Ascorbic Acid or Thermal Annealing (>)	Deoxygenated Graphitic Planes; $\sigma \sim$	Electrical network formation, piezoresistive strain sensing ¹ .
OHACB (Active Biochar)	Hemp Hurd Residuals	Slow Pyrolysis (400–600°C) + Steam	3D Hierarchical Micro/Mesoporous Particles	Internal curing water retention,

		Activation		stress damping, matrix density reduction ¹ .
OHSCF (Short Carbon Fibers)	Long Hemp Bast Fibers	Continuous Tension Carbonization (1000–1400° C)	Diameter: 5–15 μm ; Length: 1–6 mm	Macro-crack bridging, Kelly-Tyson shear lag load transfer ¹ .

Cross-Matrix Integration Mechanics and Performance Upgrades

Matrix Class	Carbon Filler Combination	Interfacial Bonding Mechanism	Key Mechanical/Functional Metric Improvements	Primary Engineering Limitation
Thermoset Epoxy	OHGO (0.5 wt%)	Epoxy-amine nucleophilic ring opening	Fracture Toughness (K_{Ic}): +65% [cite: 1]	High resin viscosity at elevated filler loading ¹ .
Hempoxy Vitrimer	OHGO + OHCNS	Dynamic hydroxyl transesterification	Flexural Modulus: +40%; Retains reprocessability ¹	Transesterification kinetics require thermal activation ⁴ .
Thermoplastic (PLA)	OHCNS (0.5 wt%)	Heterogeneous crystal nucleation	Heat Deflection Temp (HDT): > [cite: 1]	Requires high shear dispersion during compounding ¹ .
Elastomer	OHRGO (	Physical	Sensor Gauge	Cyclical strain

(TPU)	<)	entrapment / sp^2 contact networks	Factor: > [cite: 1]	degradation of conductive paths ¹ .
Geopolymer / Cement	OHACB + OHGO + OHSCF	C-S-H gel nucleation & fiber bridging	28-Day Compressive: +35%; Flexural: +50% [cite: 1]	Alkali sensitivity of non-carbonized residual organics ¹ .
Metals (Al Alloys)	OHCNS	Grain boundary pinning via SPS	Yield Strength: +30%; Grain coarsening inhibition ¹	High-temperature carbide formation (Al_4C_3) ¹ .

Feasibility, Industrial Scalability, and Risk Analysis

Translating TR-OHGCM-2026-001 from a R&D proposal into commercial manufacturing involves processing, environmental, and raw material factors¹.

Corrosive Chemical Effluent Management

Chemical activation using KOH at 1:4 impregnation ratios and modified Hummers oxidation utilizing concentrated H_2SO_4 and $KMnO_4$ generate hazardous waste streams¹. Industrial scale-up requires closed-loop acid recovery, neutralization infrastructure, and advanced wastewater treatment to process high Chemical Oxygen Demand (COD) and heavy metal effluents¹⁸.

Thermal Energy Requirements

High-temperature processing stages—including hydrothermal carbonization ($200^{\circ}C$), activation ($900^{\circ}C$), and fiber carbonization ($1400^{\circ}C$)—demand high thermal energy inputs¹. Achieving carbon-neutral operation requires utilizing waste heat recovery systems and combusting volatile pyrolysis gases (syngas) to power thermal reactors²⁵.

Biomass Feedstock Variability

Lignin, cellulose, and inorganic ash contents in industrial hemp vary across cultivars, soil conditions, and retting quality². Industrial quality control requires standardized chemical

pretreatment protocols (such as acid leaching) to remove silica, calcium, and iron impurities prior to carbonization, ensuring consistent graphitic purity across production batches¹⁸.

Conclusions and Strategic Recommendations

Proposal TR-OHGCM-2026-001 details an integrative multi-scale bio-carbon framework that unifies five organic hemp-derived carbon allotropes across seven composite matrix classes¹. While claims of absolute priority must be contextualized against existing literature on hemp carbon nanosheets, biochar-derived GO, and commercial hemp vitrimers¹, the technical design provides a structured pathway for sustainable composite engineering¹.

Four actionable R&D recommendations emerge from this evaluation:

1. **Incorporate Thermal Pre-Graphitization:** Introduce a thermal annealing step ($> 1200^{\circ}\text{C}$) for hemp hurd biochar prior to modified Hummers oxidation⁵. This increases sp^2 crystallite domain size (L_a), improving OHGO sheet dimensions and yields while preventing over-oxidation into zero-dimensional quantum dots⁵.
2. **Apply Non-Linear Percolation Modeling:** Supplement the Phase II statistical optimization framework by pairing quadratic polynomial RSM with sigmoidal power-law models⁶. This resolves mathematical fitting errors near critical electrical and rheological percolation thresholds in OHRGO-reinforced systems⁶.
3. **Evaluate Dynamic Bonding Kinetics in Hempoxy Vitrimers:** Conduct dynamic mechanical thermal analysis (DMTA) on OHGO-reinforced epoxidized hempseed oil networks to map transesterification activation energies (E_a) and topology freezing temperatures (T_v)⁴. This ensures nanofiller surface functionalization enhances mechanical modulus without impeding stress relaxation or thermal reprocessability¹.
4. **Implement Closed-Loop Chemical Recovery:** Integrate KOH recovery circuits and adopt green reduction pathways (such as L-ascorbic acid or solvothermal reduction) to minimize hazardous waste generation across the material processing lifecycle¹.

Works cited

1. Organic_Hemp_Graphitic_Composite_Materials_Revolution.pdf
2. Hemp Fibres: Essentials, Composites or Nanocomposites and, <https://unisapressjournals.co.za/index.php/NH/article/download/13835/7390/77496>
3. Synthesis Method of Hemp-Derived Graphene - ResearchGate, https://www.researchgate.net/publication/360884260_Synthesis_Method_of_Hemp-Derived_Graphene
4. Hemp Vitrimer Protocol | PDF - Scribd, <https://www.scribd.com/document/1050525728/Hemp-Vitrimer-Protocol>
5. (PDF) Biochar as an Effective Alternative to Graphite for Graphene, https://www.researchgate.net/publication/402303391_Biochar_as_an_Effective_Alternative_to_Graphite_for_Graphene_Oxide_Synthesis

6. Testing, Experimental Design and Numerical Analysis of Nano, <https://www.preprints.org/manuscript/202411.1537>
7. Synthesis of graphene oxide and graphene quantum dots ... - PMC, <https://pmc.ncbi.nlm.nih.gov/articles/PMC8044699/>
8. Non-functionalized oil palm waste-derived reduced graphene oxide, <https://arabjchem.org/non-functionalized-oil-palm-waste-derived-reduced-graphene-oxide-for-methylene-blue-removal-isotherm-kinetics-thermodynamics-and-mass-transfer-mechanism/>
9. Recent advances in cannabis and hemp research, <https://www.acs.org/pressroom/presspacs/2023/october/recent-advances-in-cannabis-and-hemp-research.html>
10. Effect of Alkaline Treatment and Graphene Oxide Coating on, <https://www.tandfonline.com/doi/abs/10.1080/15440478.2022.2053265>
11. Effect of Alkaline Treatment and Graphene Oxide Coating on, <https://www.tandfonline.com/doi/full/10.1080/15440478.2022.2053265>
12. Investigation of flexural properties of epoxy composite by utilizing, <https://opus.lib.uts.edu.au/bitstream/10453/159256/2/09673911221093646.pdf>
13. ZILA BioWorks - Game Changers | Natural Products Canada, <https://canadiangamechangers.ca/profile/zila-bioworks/>
14. ZILA Bioworks / Brand Story - Ideas For The People, <https://www.ideas4thepeople.com/work/zilabioworks-brandstory>
15. Marie-Soleil Seshat Landry, <https://marie-soleil.cv/>
16. ZILA Works Converts Plants to Resin for Spectrum of Uses, <https://calgary.tech/2023/02/01/zila-works-converts-plants-to-resin/>
17. Synthesis of Highly Porous Graphene Oxide-PEI Foams for ... - MDPI, <https://www.mdpi.com/2073-4360/16/21/2983>
18. An Update on Graphene Oxide: Applications and Toxicity - PMC, <https://pmc.ncbi.nlm.nih.gov/articles/PMC9558614/>
19. Perspective Chapter: Modification of Graphene Oxide, Graphitic, <https://www.intechopen.com/chapters/1221598>
20. Ultrasonics Sonochemistry - UNNC Research Portal, <https://research.nottingham.edu.cn/files/31557857/main.pdf>
21. (PDF) Optimal Design of Carbon-Based Polymer Nanocomposites, https://www.researchgate.net/publication/369356028_Optimal_Design_of_Carbon-Based_Polymer_Nanocomposites_Preparation_Based_on_Response_Surface_Methodology
22. Experimental, Theoretical and Simulation Studies on the Thermal, <https://pmc.ncbi.nlm.nih.gov/articles/PMC8226525/>
23. A review and analysis of electrical percolation in carbon nanotube, https://www.researchgate.net/publication/222400846_A_review_and_analysis_of_electrical_percolation_in_carbon_nanotube_polymer_composites
24. A Combined Experimental, Theoretical, and Simulation Approach to, <https://pmc.ncbi.nlm.nih.gov/articles/PMC12611060/>
25. ZILA BioWorks - ISC3, <https://www.isc3.org/page/news/zila-bioworks>