

LANDRY BIOMAT: MASTER BUSINESS PLAN & TECHNICAL SPECIFICATIONS

**Systemic Displacement of Softwood Forestry, Petrochemicals,
and Consumer Products via a 500,000-Acre Integrated Organic
Hemp Biorefinery Ecosystem in New Brunswick**

Prepared For: Regional Industrial Scale-Up & National Bio-Economy Transformation

Entity: Landry Industries Inc. / Landry BioMat Division

Biorefinery Location: Moncton, New Brunswick, Canada

Cultivation Footprint: 500,000 Acres (202,343 Hectares), Saint John & Kennebecasis
River Valleys

Author: Marie-Soleil Seshat Landry (CEO, Landry Industries Inc.)

Effective Date: July 2026

Regulatory Frameworks: Industrial Hemp Regulations (SOR/98-156), Pulp and Paper
Effluent Regulations (SOR/92-269), Canadian Environmental Protection Act (S.C. 1999, c.
33), Food and Drugs Act (FDA CFR 176.170)

Abstract

Landry Industries Inc. presents the definitive master business plan and technical specifications for **Landry BioMat**, a 500,000-acre vertically integrated organic hemp agriculture and industrial processing biorefinery anchored in Moncton, New Brunswick. Designed as a direct, full-portfolio competitive displacement mechanism against legacy softwood forestry and petrochemical conglomerates (specifically J.D. Irving Limited's non-marine divisions), Landry BioMat replaces clear-cut logging, synthetic plastics, petroleum fuels, and synthetic absorbent products with 100% organic, carbon-negative agricultural hemp counterparts. Operating with zero-liquid-discharge (ZLD) closed-loop Soda-Anthraquinone (Soda-AQ) pulping, advanced Hempoxies vitrimer chemistry, engineered structural materials, and multi-vector biofuel distillation, this blueprint outlines the technical parameters, operating standard operating procedures (SOPs), capital architecture, and environmental lifecycle metrics required to power industries across Canada.

Contents

1	Executive Summary & Core Strategic Vision	2
1.1	Venture Identity & The 500,000-Acre Imperative	2
1.2	Competitive Displacement Matrix: Landry BioMat vs. J.D. Irving Limited . . .	2
2	Upstream Agricultural Architecture (500,000 Acres)	2
2.1	Agronomic Footprint & Soil Mechanics	3
2.2	Cultivar Selection & Biomass Yield Dynamics	3
2.3	Field Retting, Primary Decortication & Fiber Separation	3
3	Moncton Central Biorefinery Architecture	4
3.1	Facility Footprint & Logistics Infrastructure	4
3.2	Soda-Anthraquinone (Soda-AQ) Pulping Division	4
3.3	Black Liquor Recovery & Zero-Liquid-Discharge (ZLD) Loop	4
4	Standard Operating Procedures across Product Vectors	5
4.1	SOP-001: Comprehensive Pulp, Paper, Tissue & Absorbent Hygiene	5
4.1.1	Scope & Manufacturing Lines	5
4.1.2	Tissue & Personal Care Operations	5
4.1.3	Bleaching & Sizing Parameters	5
4.2	SOP-002: Advanced Structural Materials & Hempoxies Vitrimers Composites . .	5
4.2.1	Parametric Mother-of-SOP Framework	5
4.2.2	Constituent Synthesis Protocols	5
4.2.3	Mass Balance Curing Equations	6
4.3	SOP-003: Engineered Wood, Hempwood & Insulation Building Systems	6
4.3.1	Hempwood & Structural Presswood Production	6
4.3.2	Hempcrete Building Blocks & Thermal Panels	6
4.4	SOP-004: Biofuels, Renewable Natural Gas & Bio-Petrochemical Substitutes . .	7
4.4.1	Cellulosic Ethanol via Hemicellulose Hydrolysis	7
4.4.2	Hempseed Biodiesel Transesterification	7
4.4.3	Renewable Natural Gas (RNG) via Anaerobic Digestion	7
5	Financial Architecture & Market Projections	7
5.1	Capital Expenditure (CAPEX) Phasing	7
5.2	Operating Expenditure (OPEX) & COGS Breakdown	7
5.3	Revenue Projections & EBITDA Margin Sensitivity	8
6	Regulatory Compliance & Environmental Metrics	8
6.1	Regulatory Framework Approvals	8
6.2	Net-Negative Carbon Lifecycle vs. Clear-Cut Forestry	9

1 Executive Summary & Core Strategic Vision

1.1 Venture Identity & The 500,000-Acre Imperative

Landry Industries Inc. establishes ****Landry BioMat****, a vertically integrated industrial manufacturing ecosystem across 500,000 acres (202,343 hectares) of certified organic agricultural land in the Saint John River Valley, Kennebecasis Valley, and surrounding agricultural regions of New Brunswick. Anchored by a central multi-vector biorefinery complex in Moncton, NB, Landry BioMat transitions regional manufacturing away from 40-year softwood timber rotations and petroleum extraction into a rapid 120-day renewable agricultural cycle.

1.2 Competitive Displacement Matrix: Landry BioMat vs. J.D. Irving Limited

J.D. Irving Limited maintains a dominant vertical monopoly across Atlantic Canada, spanning timberlands, pulp and paper mills, tissue manufacturing (Royale), private-label absorbent products (diapers), corrugated packaging, sawmills, engineered wood, and petroleum refining (Irving Oil). Landry BioMat provides an end-to-end organic, tree-free, and petroleum-free direct replacement for every non-marine division in Irving’s portfolio.

Table 1: Systemic Displacement Matrix: Landry BioMat Counterparts vs. Irving Legacy Lines

Industrial Division	Irving Legacy Product Line	Landry BioMat Organic Alternative	Key Technological Advantage
Consumer Tissue	Royale Bath/Facial/Napkin; LDC/TAD	100% Organic Hemp Soft-Tissue	Zero clear-cut pulp; ECF H ₂ O ₂ bleached; plant starch binders
Absorbent Hygiene	Private-Label Diapers & Training Pants	Organic Bast Fluff Pulp + Bio-Barrier	Biodegradable absorbent core; zero petrochemical polymers
Publishing & Offset	Softwood Kraft Offset Paper	Soda-AQ Unbleached/Bleached Hemp Offset	45% higher tensile strength; 100+ yr archival durability
Corrugated Packaging	Softwood Test Liner & Medium	Ultra-High Tear Resistance Hemp Kraft	Test Liner TL-350–500; superior wet-strength bursting
Lumber & Wood	Softwood Dimensional Lumber & Plywood	Engineered Hempwood & Presswood	20% higher Janka hardness; non-toxic soy/vitrimer binder
Structural Resins	Petrochemical Epoxies & Resins	Hempoxies Vitrimer Bionanocomposites	Reversible covalent bonding; recyclable; 100% bio-precursors
Building Insulation	Fiberglass & Rigid Foam Insulation	Hempcrete Blocks & Micro-Char Panels	Carbon-negative building envelope; R-2.1/inch insulation value
Energy & Fuels	Irving Oil Gasoline, Diesel, & Heating Oil	Cellulosic Ethanol, Biodiesel, & RNG	Net CO ₂ negative lifecycle; zero sulfur/aromatic emissions

2 Upstream Agricultural Architecture (500,000 Acres)

2.1 Agronomic Footprint & Soil Mechanics

The 500,000-acre footprint represents approximately 10% to 11% of New Brunswick's total agricultural and arable land potential, operating at 5% to 9% of the acreage controlled by traditional forest monopolies while delivering equivalent usable dry biomass.

- **Geographic Distribution:** Primary production zones span the Saint John River Valley (Carleton, York, Sunbury, Queens counties) and Kennebecasis Valley (Kings County), with regional consolidation hubs feeding the central Moncton Biorefinery via rail and high-capacity transport corridors.
- **Soil Requirements:** Well-drained loamy soils with pH 6.0–7.5. Deep taproot penetration (up to 2.0 meters) alleviates subsoil compaction, enhances drainage, and mobilizes insoluble phosphorus.
- **Crop Rotation & Organic Integrity:** 100% certified organic protocol under the Canadian Organic Standards (CAN/CGSB-32.310). Rotated in 3-year cycles with nitrogen-fixing legumes (red clover, alfalfa) and cover crops (winter rye) to eliminate synthetic pesticides, herbicides, and chemical fertilizers.

2.2 Cultivar Selection & Biomass Yield Dynamics

High-density planting protocols prioritize fiber-optimized monoecious and dioecious industrial hemp varieties approved on Health Canada's List of Approved Cultivars.

$$\text{Total Straw Yield} = A \times Y_{\text{straw}} = 202,343 \text{ ha} \times 10.0 \text{ tonnes/ha} = 2,023,430 \text{ dry tonnes/year} \quad (1)$$

- **Primary Cultivars:** *Bialobrzeskie* (dioecious, 28–32% bast yield), *Finola* (monoecious, dual-purpose grain/fiber), *NWG 2463* (dioecious fiber-type), and *CFX-2*.
- **Biomass Partitioning:** Stalk dry matter comprises 25% outer bast fiber (long, high tensile strength) and 75% inner woody hurd (short, high lignin/cellulose core).
- **Annual Feedstock Output Across 500,000 Acres:**
 - **Bast Fiber (Raw):** 505,857 dry tonnes/year.
 - **Woody Hurd (Raw):** 1,517,573 dry tonnes/year.
 - **Hempseed Oil / Cake Byproduct:** 150,000 tonnes grain yielding 45,000 tonnes seed oil + 105,000 tonnes high-protein seed cake.

2.3 Field Retting, Primary Decortication & Fiber Separation

Harvesting occurs at early flowering (70–90 days post-seeding) using specialized mechanical swathers to preserve fiber bundle alignment.

1. **Field Retting:** Swathed stalks undergo 14–21 days of controlled field retting under maritime moisture (RH 70–85%). Pectinase action by *Bacillus* and *Clostridium* species weakens pectin bonds between bast and hurd.
2. **Bale Conditioning:** Round/square bales (500–800 kg) are thermally dried to $\leq 12\%$ moisture content in continuous rotary drum dryers (80–100°C).

3. **Multi-Stage Decortication:** Conditioned stalks pass through primary industrial flail/hammer mills and secondary pin mills with adjustable gap clearances (8–12 mm) at a rate of 500–800 kg/hour per module.
4. **Pneumatic Separation:** High-velocity cyclone aspiration (≥ 20 m/s) segregates low-density bast fibers ($\rho \approx 1.4\text{--}1.5$ g/cm³) from high-density hurds ($\rho \approx 1.1\text{--}1.3$ g/cm³), achieving $\geq 95\%$ bast purity.


3 Moncton Central Biorefinery Architecture

3.1 Facility Footprint & Logistics Infrastructure

The Moncton Central Biorefinery occupies a 250-acre heavy industrial site in Moncton, New Brunswick, situated at the geographic rail and transport crossroads of Atlantic Canada. The site includes direct Class-1 CN rail siding, high-voltage hydroelectric interconnections, and dedicated industrial water recovery infrastructure.

3.2 Soda-Anthraquinone (Soda-AQ) Pulping Division

To eliminate the toxic organosulfur emissions (methyl mercaptan, hydrogen sulfide) and dioxin liabilities associated with legacy Kraft pulping, the facility utilizes the clean Soda-Anthraquinone (Soda-AQ) process.




- **Digester Configuration:** Continuous vertical hydraulic pressure vessels operating at 160°C for 45–60 minutes under 0.8 MPa (8 bar) pressure.
- **Chemical Charge:** 15% active alkali (as NaOH equivalents) derived from regional hydroelectric-powered chlor-alkali regeneration; 0.1% w/w anthraquinone (AQ) redox catalyst.
- **Liquor-to-Solids Ratio:** 4:1.
- **Yield & Kappa Metrics:** Screened pulp yield of 48%–54% with Kappa numbers ranging from 12 to 16 and intrinsic viscosity ≥ 700 cm³/g.

3.3 Black Liquor Recovery & Zero-Liquid-Discharge (ZLD) Loop

Spent pulping liquor (black liquor) undergoes 5-stage countercurrent washing and multi-effect evaporation to achieve 65% to 70% dissolved solids concentration.

1. **Recovery Boiler Combustion:** Concentrated black liquor is incinerated in a high-efficiency recovery boiler, recovering inorganic chemicals as a molten smelt (Na₂CO₃) while generating high-pressure steam (4.0 MPa, 400°C) to drive cogeneration turbines.
2. **Causticization (Lime Cycle):** Dissolved smelt (green liquor) reacts with reburned lime (CaO) to regenerate sodium hydroxide (NaOH) cooking liquor at an 85% to 92% closed-loop recovery efficiency:



3. **Zero-Liquid-Discharge (ZLD):** Process water is continuously purified through multi-stage reverse osmosis (RO) and mechanical vapor recompression (MVR) evaporators, recycling 100% of process water back to the pulping loop.

4 Standard Operating Procedures across Product Vectors

4.1 SOP-001: Comprehensive Pulp, Paper, Tissue & Absorbent Hygiene

4.1.1 Scope & Manufacturing Lines

Covers the production of commercial offset, newsprint, packaging, tissue, and personal hygiene absorbent cores.

4.1.2 Tissue & Personal Care Operations

- **Bathroom Tissue & Napkins:** Refining mixed bast/hurd pulp to 450–550 mL Canadian Standard Freeness (CSF). Sheet formation on high-speed Fourdrinier wires followed by creping on a 4.0-meter Yankee Dryer (160–180°C) with ceramic doctor blades to control creping ratio (20–40%).
- **Organic Diapers & Absorbent Hygiene (Irving Diaper Displacement):** Processing raw bast fibers via specialized mechanical defibrators to create ultra-soft, high-loft bio-fluff pulp. The absorbent core combines hemp fluff pulp with plant-derived starch superabsorbent polymers (SAP), wrapped in a 100% compostable PLA/hemp non-woven outer layer.

4.1.3 Bleaching & Sizing Parameters

Elemental Chlorine-Free (ECF) hydrogen peroxide bleaching sequence:

- **Stage 1 (H_2O_2):** 10–15 kg/tonne H_2O_2 at pH 9.5–10.0, 60°C for 2–3 hours, achieving 85–88 ISO brightness.
- **Sizing & Wet Strength:** Replacement of synthetic PAE resins with plant starches (5–8 kg/tonne) and chitosan (2–3 kg/tonne); Alkyl Ketene Dimer (AKD) emulsion at 8–12 kg/tonne for alkaline sizing (pH 7.5–8.0).

4.2 SOP-002: Advanced Structural Materials & Hempoxies Vitrimers Composites

4.2.1 Parametric Mother-of-SOP Framework

Hempoxies represent dynamic covalent vitrimer networks reinforced with bio-derived nanocarbons, fully defined by the state-space vector $\mathbf{V}$:

$$\mathbf{V} = [\text{VAR_ID}, M_k, P_i, H_h, C_m, S_s, \phi_C, \chi_c] \quad (4)$$

Where M_k is the dynamic exchange pathway, P_i is the precursor monomer, H_h is the dynamic hardener, C_m is the carbon morphology, S_s is the surface agent, ϕ_C is the carbon mass fraction ($0.0 \leq \phi_C \leq 0.30$), and χ_c is the catalyst loading ($0.00 \leq \chi_c \leq 0.05$).

4.2.2 Constituent Synthesis Protocols

1. **Precursor Monomer P_{01} (Epoxidized Hempseed Oil - EHSO):** React cold-pressed hempseed oil with performic acid generated *in situ* (0.5 mol/mol C=C) at 40–50°C. Control 30% H_2O_2 addition rate ≤ 2.0 mL/min. Vacuum dry at 70°C, 10 mbar to yield oxirane oxygen content of 6.5%–8.2% (EEW = 195–240 g/eq).
2. **Carbon Morphology C_{03} (2D Exfoliated Carbon Nanosheets - 2D-HCN):** Subject bast fiber micro-fibrils to Hydrothermal Carbonization (HTC) in 0.5 M H_2SO_4 at 180°C for 24 hours. Mix hydrochar with KOH (1:4 ratio) and pyrolyze under Argon

at 800°C for 2 hours (5°C/min ramp). Yields high-surface-area nanosheets ($S_{\text{BET}} \geq 800 \text{ m}^2/\text{g}$).

3. **Surface Functionalization S_01 (GPTMS Silanization):** Disperse 2D-HCN in ethanol/water (90:10) via probe sonication. Add 3-Glycidyloxypropyltrimethoxysilane (50 wt% relative to carbon), adjust pH to 4.5 with acetic acid, and reflux at 75°C for 6 hours.

4.2.3 Mass Balance Curing Equations

Given target composite batch mass M_{total} :

$$M_{\text{carbon}} = M_{\text{total}} \times \phi_C, \quad M_{\text{catalyst}} = (M_{\text{total}} - M_{\text{carbon}}) \times \chi_c \quad (5)$$

$$M_{\text{precursor}} = (M_{\text{total}} - M_{\text{carbon}} - M_{\text{catalyst}}) \times \left[\frac{\text{EEW}(P_i)}{\text{EEW}(P_i) + r \cdot \text{HEW}(H_h)} \right] \quad (6)$$

$$M_{\text{hardener}} = (M_{\text{total}} - M_{\text{carbon}} - M_{\text{catalyst}}) \times \left[\frac{r \cdot \text{HEW}(H_h)}{\text{EEW}(P_i) + r \cdot \text{HEW}(H_h)} \right] \quad (7)$$

Execute cure schedule $T_{\text{cure}}(t)$ in a heated hydraulic press under 5 MPa pressure: 80°C for 1 hour, 140°C for 2 hours, and post-cure at 160°C for 1 hour to induce transesterification network formation.

4.3 SOP-003: Engineered Wood, Hempwood & Insulation Building Systems

4.3.1 Hempwood & Structural Presswood Production

Directly replaces Irving sawmills, dimensional lumber, and particleboard facilities.

1. **Mat Preparation:** Cleaned hurd fragments (70%) and long bast fiber bundles (30%) are blended with non-toxic, soy-based or Hempoxies vitrimer binders (8–12 wt% resin charge).
2. **Compression Molding:** The mass is compressed in a continuous multi-daylight hydraulic steam-heated press at 180–210°C under 3.5–5.0 MPa consolidation pressure.
3. **Performance Standards:** Yields structural beams and boards with Janka hardness exceeding 1,400 lbf (20% harder than traditional white oak/softwood) and modulus of elasticity $E \geq 3.2 \text{ GPa}$.

4.3.2 Hempcrete Building Blocks & Thermal Panels

- **Formulation:** Purified inner hurds (1.0 m³) combined with hydrated lime binder (200 kg Ca(OH)₂), hydraulic lime (50 kg), and water (250 L).
- **Block Molding:** Formed via low-pressure vibration compaction into interlocking construction blocks (300 mm × 200 mm × 600 mm).
- **Curing & Performance:** Carbonation curing over 28 days consumes atmospheric CO₂. Delivers density of 280–340 kg/m³, thermal conductivity $\lambda = 0.06\text{--}0.08 \text{ W/m} \cdot \text{K}$ (R-2.1/inch), and Class-A fire resistance.

4.4 SOP-004: Biofuels, Renewable Natural Gas & Bio-Petrochemical Substitutes

4.4.1 Cellulosic Ethanol via Hemicellulose Hydrolysis

Pre-pulping liquor rich in extracted hemicellulose undergoes acid hydrolysis (0.5% H₂SO₄, 120°C) followed by enzymatic saccharification using *Trichoderma reesei* cellulase complexes. Fermentation with engineered *Saccharomyces cerevisiae* yields cellulosic ethanol distilled to 99.8% purity for industrial fuel blending.

4.4.2 Hempseed Biodiesel Transesterification

Excess seed oil is transesterified with bio-ethanol using potassium hydroxide (1.0 wt%) catalyst at 60°C for 2 hours, yielding fatty acid ethyl esters (FAEE) meeting ASTM D6751 biodiesel standards, with crude glycerol recovered for industrial applications.

4.4.3 Renewable Natural Gas (RNG) via Anaerobic Digestion

Biorefinery organic wastes, wastewater sludge, and field residues enter high-rate mesophilic (37°C) continuous stirred-tank anaerobic digesters. The produced biogas (60% CH₄, 40% CO₂) undergoes membrane separation to produce pipeline-grade RNG (≥ 97% CH₄) injected directly into regional natural gas networks.

5 Financial Architecture & Market Projections

5.1 Capital Expenditure (CAPEX) Phasing

The integrated industrial complex requires a total capital commitment of \$48.5M for the initial phase, scaling to \$250M–\$450M for full 500,000-acre capacity expansion over 5 years.

Table 2: Phase 1 Capital Expenditure Breakdown (Moncton Central Biorefinery)

Capital Category	Est. Cost (CAD M)	Primary Assets / Machinery
Site Acquisition & Civil Works	\$8.5	250-acre site, rail siding, water treatment pads
Decortication & Fiber Cleaning	\$4.5	Multi-stage hammer/pin mills, cyclone separators
Soda-AQ Digesters & Recovery Boiler	\$12.0	Vertical continuous pressure vessels, lime kiln, ZLD RO system
Paper & Tissue Machines	\$16.0	Fourdrinier wire section, Yankee creping dryer, calender stacks
Hempoxies & Composite Line	\$4.5	High-shear reactors, hydraulic press lines, autoclave units
QA/QC Lab & Regulatory Testing	\$3.0	Analytical instruments (FTIR, TGA, DSC, DMA, OECD 203)
TOTAL PHASE 1 CAPEX	\$48.5 M	Integrated 50,000-tonne initial capacity

5.2 Operating Expenditure (OPEX) & COGS Breakdown

At full operational volume (750,000 tonnes finished paper/packaging/tissue output from scaled operations), manufacturing COGS averages \$626.80 per tonne.

Table 3: Scaled Operating Cost (COGS) Structure at 750,000 Tonnes/Year Output

Cost Component	Annual Total (CAD M)	Cost per Tonne (CAD)	% of COGS
Upstream Feedstock (Cultivation, Harvest, Retting)	\$385.0	\$513.33	81.9%
Chemicals & Additives (NaOH, AQ, H ₂ O ₂ , Starch)	\$0.15	\$0.20	0.05%
Utilities (Energy, Steam, MVR Water Recovery)	\$53.0	\$70.67	11.3%
Direct Operations & Maintenance Labor (350 FTE)	\$32.0	\$42.67	6.8%
TOTAL MANUFACTURING COGS	\$470.15 M	\$626.80	100.0%

5.3 Revenue Projections & EBITDA Margin Sensitivity

Operating across a diversified product mix yields a blended Average Selling Price (ASP) ranging from \$1,150/tonne (commodity offset/packaging) to \$1,787/tonne (specialty art, luxury packaging, and Hempoxies vitrimers).

Table 4: 5-Year Financial Scale-Up Model (2026–2031)

Financial Metric	Year 1	Year 2	Year 3	Year 4	Year 5
Cultivation Footprint (Acres)	15,000	50,000	150,000	300,000	500,000
Finished Product Output (Tonnes)	22,500	75,000	225,000	450,000	750,000
Blended ASP (CAD/Tonne)	\$1,450	\$1,350	\$1,250	\$1,180	\$1,150
Gross Revenue (CAD M)	\$32.63	\$101.25	\$281.25	\$531.00	\$862.50
Total Manufacturing COGS (CAD M)	\$16.20	\$50.25	\$141.03	\$282.06	\$470.15
Gross Profit (CAD M)	\$16.43	\$51.00	\$140.22	\$248.94	\$392.35
Gross Margin %	50.3%	50.4%	49.9%	46.9%	45.5%
SG&A and R&D Opex (CAD M)	\$8.50	\$18.00	\$35.00	\$55.00	\$80.00
EBITDA (CAD M)	\$7.93	\$33.00	\$105.22	\$193.94	\$312.35
EBITDA Margin %	24.3%	32.6%	37.4%	36.5%	36.2%

Simple capital payback on the initial \$48.5M Phase 1 investment is achieved within 22 months of commercial operations.

6 Regulatory Compliance & Environmental Metrics

6.1 Regulatory Framework Approvals

- Health Canada Industrial Hemp Licensing:** Compliance with Industrial Hemp Regulations (SOR/98-156) under the Cannabis Act. Annual Notice of Cultivation reporting, GPS field boundaries, and certified THC monitoring below 0.3% w/w dry weight.
- Pulp and Paper Effluent Regulations (PPER, SOR/92-269):** Continuous compliance monitoring for discharged effluent:
 - Biochemical Oxygen Demand (BOD₅):** < 25 mg/L.
 - Total Suspended Solids (TSS):** < 20 mg/L.
 - Acute Fish Toxicity:** Zero mortality in 100% unheated mill effluent under 96-hour OECD 203 testing protocol (*Leuciscus idus* / *Oncorhynchus mykiss*).

3. **Canadian Environmental Protection Act (CEPA):** New Substances Notification (NSN) filings for functionalized bio-monomers (EHSO, CHSO) prior to commercial volumes exceeding 100 kg/year.
4. **Food and Drug Administration (FDA):** Compliance with FDA CFR 176.170 for food-contact paperboard and packaging materials.

6.2 Net-Negative Carbon Lifecycle vs. Clear-Cut Forestry

$$\text{Net Carbon}_{\text{Hemp}} = \text{Sequestration}_{\text{Field}} - \text{Emissions}_{\text{Processing}} = -830,000 + 330,000 = -500,000 \text{ tonnes CO}_2\text{-eq/y} \quad (8)$$

Table 5: Annual Carbon Footprint Comparison: 500,000 Acres Hemp vs. Equivalent Softwood Logging

Lifecycle Stage	Softwood Forestry (Irving Clear-Cut)	Landry BioMat (Agricultural Hemp)
Harvest / Sequestration Cycle	40-year rotation; releases 50–100 t CO ₂ /ha	120-day crop; sequesters 8–12 t CO ₂ /ha/yr
Net Photosynthetic Capture	+25,000,000 t CO ₂ over 40 yrs	–830,000 t CO ₂ /year captured directly
Pulping & Processing Energy	0.75 t CO ₂ /tonne (Kraft fossil steam)	+325,000 t CO ₂ /year (Offset by biomass boiler)
Agricultural / Transport Inputs	Heavy equipment, road building, logging	+6,200 t CO ₂ /year (Agricultural machinery)
NET ANNUAL CARBON BALANCE	+625,000 to 1,400,000 t CO ₂ /yr	–500,000 tonnes CO ₂ -eq/year (NET NEGATIVE)

Operating 500,000 acres of organic hemp delivers an annual net carbon delta of **1.125 to 1.900 million tonnes of CO₂ avoided** relative to clear-cut softwood harvesting.

References

- [1] Government of Canada, *Industrial Hemp Regulations (SOR/98-156)*, updated under the Cannabis Act, Health Canada, Ottawa, ON, 2024.
- [2] Environment and Climate Change Canada, *Pulp and Paper Effluent Regulations (SOR/92-269)*, Canadian Environmental Protection Act, 1992 (amended 2022).
- [3] Government of Canada, *Canadian Environmental Protection Act (S.C. 1999, c. 33)*, Minister of Justice, Ottawa, ON, 1999.
- [4] D. Montarnal, M. Capelot, F. Tournilhac, and L. Leibler, “Silica-like malleable materials from permanent organic networks,” *Science*, vol. 334, no. 6058, pp. 965–968, 2011.
- [5] H. Wang, Z. Xu, A. Koh, X. Li, K. O. Fayot, and D. Mitlin, “Interconnected carbon nanosheets derived from hemp for ultrafast supercapacitors with high energy,” *ACS Nano*, vol. 7, no. 6, pp. 5131–5141, 2013.
- [6] W. Cai, Y. Huang, J. Li, G. Yang, F. Wang, and G. Si, “A multifunctional biomass zinc catalyst for epoxy-based vitrimers and composites,” *European Polymer Journal*, vol. 188, p. 111936, 2023.
- [7] R. Turco, R. Tesser, and M. Di Serio, “Kinetic and thermodynamic analysis of hemp oil epoxidation with density functional theory insights,” *Industrial & Engineering Chemistry Research*, vol. 64, no. 3, pp. 1012–1024, 2025.

- [8] J. A. Gandia, L. M. Garcia, and M. A. Rodriguez, “A critical review of industrial fiber hemp anatomy, agronomic practices, and valorization into sustainable bioproducts,” *BioResources*, vol. 16, no. 4, pp. 8500–8535, 2021.
- [9] Globe and Mail Industrial Report, *Atlantic Canada Industrial Manufacturing and Corporate Holdings: J.D. Irving Limited Financial Profile*, Financial Post Data Services, Toronto, ON, 2024.