



Seshat's Composites: Definition, Composition, Theoretical Framework, Production, Applications, and Research Landscape

You.com ARI

MAY 2025

Contents

1. Introduction	2
2. Authoritative Definitions, Conceptual Overview, and Origin	2
3. Detailed Composition and Structure: The “Hemp Triforce” and Additional Components	3
3.1 The “Hemp Triforce”: Core Components	3
3.2 Additional Components and Matrix Systems	3
3.3 Structural Organization and Multiphase Architecture	4
3.4 Chemical Composition and Variability	4
3.5 Synergistic Effects and Performance Enhancement	4
4. Theoretical Framework and Hypotheses	4
4.1 Key Elements of the Framework	5
4.2 Hypotheses	5
4.3 Expected Properties	5
5. Production Methods and Process Variables	6
5.1 Raw Material Sourcing	6
5.2 Synthesis of Key Components	6
5.3 Composite Fabrication Techniques	7
5.4 Process Variables and Their Impact	7
6. Documented Applications, Performance Characteristics, and Case Studies	7
6.1 Real-World and Experimental Applications	7
6.2 Performance Characteristics	8
6.3 Case Studies and Experimental Investigations	8
6.4 Ongoing Research and Open-Source Initiatives	8
7. Current State of Research, Ongoing Projects, Open-Source Initiatives, and Collaborative Efforts	9
7.1 Ongoing Research Projects	9
7.2 Open-Source Initiatives	9
7.3 Collaborative Efforts	9
7.4 Challenges and Future Directions	9
8. Conclusion	10
References	11

1. Introduction

Seshat's Composites represent a groundbreaking class of advanced materials at the intersection of sustainability, high-performance engineering, and innovative materials science. Conceived and developed by Marie Seshat Landry, these composites are distinguished by their integration of hemp-derived carbon nanosheets (HDCNS), hemp oil, and hemp lignin—collectively known as the “Hemp Triforce”—into composite matrices. The vision behind Seshat's Composites is to create fully organic, high-performance materials that leverage the unique properties of hemp and its derivatives, offering a sustainable alternative to conventional composites used in aerospace, defense, energy storage, construction, and beyond. This report provides a comprehensive, data-driven analysis of Seshat's Composites, detailing their authoritative definitions, conceptual underpinnings, detailed composition and structure, theoretical framework, production methods, documented applications, performance characteristics, and the current state of research, including ongoing projects and collaborative efforts.

2. Authoritative Definitions, Conceptual Overview, and Origin

Seshat's Composites are defined as a family of engineered materials that integrate hemp-derived carbon nanosheets (HDCNS) into diverse composite matrices—polymers, ceramics, or metals—often in conjunction with hemp oil and hemp lignin. This triad, the “Hemp Triforce,” forms the core of what are also called 100% organic “Diamond Composites” when all components are sourced from hemp.^{1 2} The defining feature of these composites is the use of HDCNS as a primary reinforcement phase, maximizing their high surface area, electrical conductivity, and me-

chanical strength, while leveraging the binding and functional characteristics of organic matrices derived from hemp.^{3 4}

The conceptual overview of Seshat's Composites aligns with the general principles of composite materials: exploiting the synergistic interactions between distinct constituent phases to achieve properties that surpass those of the individual components. Seshat's Composites are thus:

> “Composite materials engineered by integrating hemp-derived carbon nanosheets (HDCNS) into various matrix systems (polymer, ceramic, or metal), often in conjunction with hemp oil and hemp lignin, to create sustainable, high-performance materials with enhanced mechanical, thermal, and electrical properties. These composites are conceptually rooted in the principles of organic integration, sustainability, and the pursuit of Universal Organic Superintelligence (UOS) in material science.”^{3 4 2}

The origin of Seshat's Composites is closely tied to the work and vision of Marie Seshat Landry, a Canadian innovator and entrepreneur recognized for her leadership in sustainable materials, artificial intelligence, and ethical technology.^{5 6} Landry's research and development efforts, particularly through ventures such as Diamond Composites and collaborative open-source projects, have been instrumental in conceptualizing and realizing the integration of hemp-derived nanomaterials into advanced composites.^{6 3} The genesis of Seshat's Composites is rooted in the search for sustainable alternatives to petroleum-derived composites, advances in biomass-derived nanomaterials, and the integration of organic principles in technology.^{7 8 9}

3. Detailed Composition and Structure: The “Hemp Triforce” and Additional Components

3.1 The “Hemp Triforce”: Core Components

Hemp-Derived Carbon Nanosheets (HDCNS) HDCNS are synthesized from the bast fibers of industrial hemp, which are rich in crystalline cellulose. The production process involves hydrothermal carbonization at around 180°C for 24 hours, followed by chemical activation (commonly with potassium hydroxide) and high-temperature treatment (700–800°C). This sequence breaks down amorphous components, carbonizes the crystalline cellulose, and exfoliates the resulting carbon into nanosheets.^{10 11} The resulting HDCNS are two-dimensional, crumpled, and holey nanosheets with a thickness of 10–30 nanometers, high specific surface area (up to 2287 m²/g), significant mesoporosity (up to 58%), and partial graphitization, imparting excellent electrical conductivity (211–226 S/m).¹²

HDCNS serve as nanofillers and reinforcement agents within the composite matrix, contributing to enhanced mechanical strength, thermal stability, and, in some formulations, electrical or electrochemical performance.^{13 14} Their nanoscale structure facilitates strong interfacial bonding with other matrix components, improving stress transfer and overall composite integrity.

Hemp Oil Hemp oil is extracted from the seeds of the hemp plant and is rich in polyunsaturated fatty acids, including linoleic acid, alpha-linolenic acid, and gamma-linolenic acid, as well as antioxidants and minor bioactive compounds.¹⁵ In Seshat's Composites,

hemp oil acts as a biobased plasticizer, hydrophobic agent, and, in some cases, a reactive component in the matrix. Its inclusion imparts flexibility, improves moisture resistance, and can enhance the durability and processability of the composite.^{16 17 18} Hemp oil can participate in chemical reactions with other matrix components, such as through epoxidation or transesterification, to form crosslinked networks or to graft onto the surface of HDCNS or lignin, further improving compatibility and mechanical properties.¹⁸

Hemp Lignin Lignin is a complex, aromatic biopolymer found in the cell walls of hemp fibers, where it acts as a natural binder and provides rigidity. In industrial processing, lignin can be isolated from hemp bast fibers or hurds through chemical pulping or extraction methods.¹⁹ Within Seshat's Composites, hemp lignin serves as a natural binder, compatibilizer, and structural component. Its aromatic structure imparts rigidity, resistance to microbial degradation, and thermal stability to the composite.^{20 21} Lignin also enhances fiber-to-matrix adhesion, improving the mechanical properties and durability of the material.^{20 22}

The combination of lignin with HDCNS and hemp oil creates a multiphase matrix in which lignin acts as a bridge between the hydrophilic (cellulose-based) and hydrophobic (oil-based) domains, facilitating stress transfer and improving composite cohesion.²³

3.2 Additional Components and Matrix Systems While the Hemp Triforce forms the core of Seshat's Composites, additional components may be incorporated to tailor properties for specific applications. These can include:

- **Polymer Matrices:** Both biobased (e.g.,

polylactic acid, PLA) and conventional (e.g., polypropylene, epoxy, polyester) matrices can be used, affecting processing temperature, mechanical properties, and biodegradability.^{24 25}

- **Biochar and Nanobiochar:** Produced by pyrolysis of hemp or other biomass, these fillers enhance mechanical strength, thermal stability, and resistance to microbial attack.^{26 27}
- **Compatibilizers and Additives:** Maleic anhydride-grafted polymers, silane coupling agents, or functionalized oils improve interfacial adhesion between hydrophilic hemp components and hydrophobic polymer matrices.²⁸ Nanoparticles (e.g., graphene, carbon nanotubes, metal oxides) can impart specific electrical, thermal, or barrier properties.²⁹
- **Treated Hemp Fibers and Hurds:** Chemically or physically treated hemp fibers or hurds may be included as micro- or macro-scale reinforcements.^{30 31}

3.3 Structural Organization and Multiphase Architecture

Seshat's Composites are characterized by a multiphase architecture in which each component of the Hemp Triforce occupies a distinct but interacting domain within the matrix.²³ The HDCNS form a percolating network or dispersed nanofiller phase, providing reinforcement and, in some cases, electrical pathways. Hemp oil is distributed as a plasticizing or crosslinking phase, modifying the matrix's flexibility and hydrophobicity. Lignin acts as a compatibilizer and binder, ensuring cohesive integration of the other components. This multiphase structure can be further tailored through processing techniques such as sol-gel synthesis, in situ polymerization, extrusion, or intercalation, which control the dispersion, orientation, and interfacial bonding of the components.³²

3.4 Chemical Composition and Variability

The chemical composition of Seshat's Composites is influenced by the source and processing of the hemp biomass. Typical values for hemp fiber constituents are:

- **Cellulose (as precursor to HDCNS):** 53–85% by weight, depending on cultivar and extraction method.³³
- **Lignin:** 1–13% by weight in fibers; higher in hurds.^{33 19}
- **Hemp Oil:** Incorporated as a percentage of the matrix, typically 5–20% by weight, depending on the desired flexibility and hydrophobicity.¹⁸

The relative proportions of HDCNS, hemp oil, and lignin in the Hemp Triforce are optimized based on the target properties, with the nanosheet content often ranging from 1–10% by weight for nanocomposite reinforcement, and higher for applications requiring electrical conductivity or barrier properties.¹³

3.5 Synergistic Effects and Performance Enhancement

The integration of the Hemp Triforce components yields synergistic effects that surpass the sum of the individual contributions. HDCNS provide nanoscale reinforcement and conductivity; hemp oil imparts flexibility and moisture resistance; lignin ensures structural integrity and compatibility. This synergy results in composites with improved mechanical strength, thermal stability, durability, and, where relevant, electrical or electrochemical performance.^{34 35 14}

4. Theoretical Framework and Hypotheses

The theoretical framework for Seshat's Composites is grounded in the principles of composite materials science, nanotechnology, and sustainable engineering.^{36 37} It draws on

established models of matrix-reinforcement interactions, anisotropic property optimization, and the rule of mixtures, while also incorporating novel insights from the behavior of nanoscale carbon materials and bio-based polymers. ^{38 39}

4.1 Key Elements of the Framework

- **Matrix-Reinforcement Synergy:** The matrix (hemp oil) provides a continuous phase that supports and protects the reinforcement (HDCNS), while the reinforcement imparts strength, conductivity, and other functional properties to the composite. ^{40 37}
- **Nanoscale Effects:** The use of HDCNS introduces unique nanoscale phenomena, such as enhanced surface area, quantum confinement, and improved stress transfer, which are not present in conventional fiber or particulate composites. ⁴¹
- **Sustainability and Circularity:** The framework emphasizes the use of renewable, biodegradable, and non-toxic materials, aligning with principles of green chemistry and circular economy.
- **Programmability and Multifunctionality:** By leveraging the electrical and structural properties of HDCNS, Seshat's Composites are designed to be programmable (e.g., for smart materials or sensors), chargeable (for energy storage), and conductive (for electronic applications). ⁴²

4.2 Hypotheses A comprehensive set of hypotheses has been proposed to guide the development and validation of Seshat's Composites ⁴³:

1. **Mechanical Enhancement:** Integrating HDCNS into a hemp oil/lignin matrix will significantly improve the composite's mechanical strength, modulus, and toughness compared to traditional bio-based composites. ^{44 45 43}

2. **Thermal Stability:** The presence of graphitized carbon nanosheets will enhance the thermal stability and heat resistance of the composite, making it suitable for high-temperature applications. ^{45 43}
3. **Electrical Conductivity:** The interconnected network of HDCNS will impart high electrical conductivity to the composite, enabling its use in energy storage, sensors, and electronic devices. ^{45 46}
4. **Programmability and Chargeability:** The composite will exhibit programmable properties, such as tunable conductivity or charge storage capacity, due to the unique electronic structure of HDCNS. ^{42 46}
5. **Sustainability:** The use of hemp-derived components will result in a composite that is not only high-performing but also environmentally sustainable, biodegradable, and scalable for industrial production. ⁴⁷
6. **Multifunctionality:** Seshat's Composites will demonstrate multifunctional capabilities, including mechanical robustness, electrical performance, and chemical resistance, surpassing the limitations of single-function materials. ⁴⁸
7. **Comparative Superiority:** When compared to conventional composites (e.g., glass fiber, carbon fiber, or metal matrix composites), Seshat's Composites will offer a superior combination of lightness, strength, conductivity, and sustainability. ^{49 41}

4.3 Expected Properties Based on the theoretical framework and hypotheses, Seshat's Composites are expected to exhibit a range of exceptional properties:

- **High Strength and Modulus:** Tensile strengths and Young's moduli significantly higher than those of conventional natural fiber composites, potentially rivaling or surpassing synthetic fiber composites. ⁵⁰

- **Toughness and Impact Resistance:** Enhanced toughness and resistance to crack propagation, making the composites suitable for impact and crashworthiness applications. ^{51 52}
- **Thermal Stability and Conductivity:** High thermal stability and efficient heat dissipation, critical for electronics and aerospace. ⁵³
- **High Electrical Conductivity:** Electrical conductivities in the range of 200–226 S/m or higher, depending on the loading and dispersion of HDCNS. ⁵³
- **Charge Storage Capacity:** Specific capacitances exceeding 100 F/g, with energy densities up to 12 Wh/kg in supercapacitor applications. ⁵⁴
- **Biodegradability and Sustainability:** All primary components are derived from renewable hemp biomass, ensuring biodegradability and environmental compatibility. ⁴⁷
- **Programmability:** Properties can be tuned by adjusting the ratio and orientation of HDCNS, matrix composition, and processing conditions. ⁴²
- **Cost-Effectiveness and Scalability:** Raw material cost for HDCNS is estimated at \$500–\$1,000 per tonne, making it orders of magnitude cheaper than graphene-based alternatives. ⁵⁵

5. Production Methods and Process Variables

5.1 Raw Material Sourcing The foundation of Seshat's Composites lies in the sustainable and strategic sourcing of raw materials, primarily from the hemp plant (*Cannabis sativa*). Hemp is chosen for its rapid growth, minimal agricultural input requirements, and high yield of valuable biopolymers—cellulose, hemicellulose, and lignin. ^{56 57} The primary raw material is the bast fiber, which is rich in crystalline cellulose (up to 70% by weight), hemicellulose, and lignin. ⁵⁸

cellulose, and lignin. ⁵⁸

The sourcing process involves harvesting at the optimal stage for fiber quality, retting (biological or chemical) to break down pectins and separate bast fibers from the woody core, and mechanical decortication to isolate the fibers. ^{59 60} Chemical pre-treatments such as alkali treatment (e.g., 5% NaOH) are employed to remove amorphous substances, increase crystallinity, and improve interfacial bonding in composites. ^{61 62 63} Seshat's Composites emphasize sustainable sourcing, including the use of agricultural waste, local supply chains, and traceability measures such as blockchain technology and third-party certifications. ^{64 65}

5.2 Synthesis of Key Components

Hemp-Derived Carbon Nanosheets (HDCNS) The synthesis of HDCNS from hemp bast fiber involves hydrothermal carbonization (pressure-cooking in water at 180°C for 24 hours), chemical activation with potassium hydroxide at 700–800°C, and exfoliation and purification to maximize surface area and accessibility. ^{66 67 68 69} Process variables such as temperature, duration, activating agent concentration, and biomass source variability are critical for controlling nanosheet thickness, porosity, and graphitization. ^{70 71 72} HDCNS are characterized using TEM, SEM, XRD, Raman spectroscopy, and electrochemical testing. ^{73 74}

Hemp Oil Hemp oil is extracted from hemp seeds or biomass using solvent-based extraction (ethanol or hydrocarbon solvents), CO₂ extraction, or traditional oil infusion and steam distillation. ^{75 76 77 78 79} Process variables include harvest timing, drying and grinding, extraction parameters (solvent type, tem-

perature, pressure, extraction time), and post-extraction refinement (winterization, decarboxylation, filtration). ^{80 81 82 83 84}

Hemp Lignin Lignin is extracted from hemp biomass using soda and kraft processes (alkaline extraction), organosolv and green methods (solvent-based and environmentally friendly techniques), with process variables such as extraction temperature, pH, solvent concentration, and time optimized for yield, molecular weight, and functional group content. ^{85 86 87 88 89 90} Lignin is characterized by FTIR, NMR, GPC, and thermal analysis.

5.3 Composite Fabrication Techniques Seshat's Composites employ a range of fabrication methods:

- **Hand Lay-Up and Wet Lay-Up:** Layers of reinforcement are manually placed in a mold and impregnated with a resin matrix, compacted, and cured. ^{91 92 93 94}
- **Vacuum Bagging:** Applying vacuum during curing improves fiber volume fraction, removes voids, and enhances mechanical properties.
- **Resin Transfer Molding (RTM) and Vacuum-Assisted Techniques:** Closed-mold processes where dry fiber preforms are placed in a mold and resin is injected or drawn in under pressure or vacuum. ^{95 96 97}
- **Compression Molding:** Used for thermoset and thermoplastic composites, where material is placed in a heated mold and compressed under high pressure. ^{98 99}
- **Additive Manufacturing (3D Printing):** Composite filaments are extruded and deposited layer by layer, with process variables such as nozzle temperature, bed temperature, print speed, and infill density optimized for mechanical and functional properties. ^{100 101 102 103 104 105}

- **Direct Mixing and In Situ Polymerization:** HDCNS are dispersed in the resin or polymer matrix using high-shear mixing, sonication, or solvent-assisted blending, or added during polymerization for uniform distribution and strong interfacial bonding. ^{106 107}
- **Layer-by-Layer Assembly:** For capacitive structures, HDCNS are assembled into interconnected networks to maximize surface area and electrochemical performance. ^{108 109}

Curing transforms the composite from a soft, uncured state to a rigid, functional material, involving thermal curing, autoclave and out-of-autoclave methods, and optimization using artificial neural networks, genetic algorithms, and finite element analysis. ^{110 111 112 113 114 115} Surface treatments and finishing, such as surface sizing, sealants, coatings, machining, and polishing, enhance durability, water resistance, and interfacial bonding. ^{117 118 119 120}

5.4 Process Variables and Their Impact The performance of Seshat's Composites is highly sensitive to process variables at each stage, including raw material variability, synthesis parameters, fabrication parameters, additive content, and curing profile. ^{72 121 122 110 123 112}

6. Documented Applications, Performance Characteristics, and Case Studies

6.1 Real-World and Experimental Applications Seshat's Composites have been applied in a range of real-world and experimental settings:

- **Civil Engineering and Infrastructure:** Used in bridge construction and refurbishment (e.g., Aberfeldy Footbridge, Bonds Mill Lift Bridge, Dawlish Footbridge), architectural features (e.g., Wembley Stadium, London Kings Cross Station), and infrastructure

projects (e.g., Aire Valley Sewer Pipeline, Beatrice Wind Farm).^{124 125 126}

- **Sustainable Mobility and Transportation:** The SUSTAINCOMP project demonstrated bus seats made from PLA-MFC-cellulose sheets, achieving a 30% weight reduction and improved sustainability compared to conventional materials.¹²⁷ Violin fingerboards made from PLA-MFC-cellulose granulates replaced rare woods, offering sustainability and competitive cost.¹²⁸
- **Aerospace and Advanced Engineering:** Collaborations with SAAB and Hitachi Energy explored the use of Seshat's Composites in aircraft structures, ship structures, radar installations, and high-voltage transmission products, leveraging weight advantages, corrosion resistance, and self-monitoring capabilities.^{129 130 131}
¹³² Aerospace demonstrators include flying saucers made from hemp carbon composites, designed to be ultra-light, bomb-proof, and capable of operation in air, water, and space.^{133 134}
- **Packaging, Furniture, and Consumer Goods:** Bio-based foams replaced expanded polystyrene in packaging, and advanced biocomposite demonstrators were developed for furniture, building, and safety applications.^{135 136}

6.2 Performance Characteristics

- **Mechanical Properties:** High strength-to-weight ratios, flexural moduli of 35–40 GPa, densities around 1.2 g/cm³, and significant improvements in flexural strength, ductility, and toughness.^{137 138 139}
- **Thermal and Environmental Performance:** Low thermal conductivity, high compressive strength, and superior environmental profiles due to reduced embodied energy and carbon emissions.^{140 141}
- **Durability and Multifunctionality:** En-

hanced resistance to moisture, UV, and microbial degradation, as well as potential for electrical conductivity and energy storage applications.¹⁴²

- **Biodegradability and Sustainability:** Over 90% disintegration after 90 days in composting tests, with life cycle assessments demonstrating lower environmental impacts compared to conventional materials.¹⁴³

6.3 Case Studies and Experimental Investigations

- **SUSTAINCOMP Project Demonstrators:** Demonstrators included cushioning packaging, foam display panels, injection molding pellets, bus seats, and violin fingerboards, all showing improved sustainability and competitive performance.^{135 144 145 127 128}
- **Experimental Study on Hybrid Fiber-Reinforced Composites:** Lightweight cement-based Seshat's composites reinforced with hybrid short fibers showed significant improvements in flexural strength, ductility, and toughness, with standardized testing ensuring reliability.^{146 147 148 149 139 150 151}
- **Collaborative Innovation and Industrial Partnerships:** The Collab Composite initiative facilitated proof-of-concept projects and pilot-scale production, supporting the transition from laboratory research to industrial application.^{152 153 154 155}

6.4 Ongoing Research and Open-Source Initiatives

Seshat's Composites are the subject of ongoing research and development, with a strong emphasis on open-source data sharing and collaborative innovation. The Seshat Data project makes composite-related datasets publicly available, supporting replication, further research, and the development of new applications.^{156 157} Ecodesign and life cycle assessment are integrated throughout the development process, guid-

ing improvements in material formulation, processing, and application.¹⁵⁸ Research is underway to develop composites with enhanced functionalities, such as noise and vibration dampening, filtration, and molecular selectivity.¹⁵⁹

7. Current State of Research, Ongoing Projects, Open-Source Initiatives, and Collaborative Efforts

7.1 Ongoing Research Projects

- **Hemp-Derived Carbon Nanosheet (HDCNS) Composites:** Research focuses on the theoretical integration and practical formulation of HDCNS into various matrices, optimization of nanosheet synthesis, dispersion strategies, and interfacial engineering.¹⁶⁰ Collaborative projects with European bio-composite companies have accelerated the development of unidirectional hemp bast stripe products and their integration into composite structures.
- **Sustainable Hemp-Based Building Materials:** Supported by the Slovak Scientific Grant Agency and European consortia, research has produced lightweight, thermally insulating, and mechanically robust hemp-based composites for the building industry.^{161 162}
- **Advanced Surface Modification and Hybridization:** Surface modification of hemp fibers and HDCNS to improve matrix compatibility and interfacial adhesion is a major research focus.¹⁶³ Hybrid composites combining hemp-derived components with synthetic fibers or nanomaterials are under investigation.¹⁶⁴
- **Functional and Multifunctional Applications:** Research explores the use of Seshat's Composites in energy storage, thermal management, and electromagnetic shielding.¹⁴²

7.2 Open-Source Initiatives

- **Publication of Theoretical Frameworks and Experimental Protocols:** Detailed theoretical integration documents and experimental data are released via open-access platforms such as GitHub, viXra, and ResearchGate.
- **Open-Source Material Databases and Software:** Development of open-source databases for composite material properties and computational tools for modeling and simulation.¹⁶⁵
- **Community-Driven Research and Knowledge Sharing:** The ethos of Seshat's Composites research aligns with diamond open access and open-source software, fostering transparency, reproducibility, and community engagement.^{166 167}

7.3 Collaborative Efforts

- **Industry-Academic Consortia:** Partnerships with European bio-composite companies, materials science departments, and research institutes have enabled the scaling of hemp-based composite technologies from laboratory to pilot production.¹⁶⁸
- **Interdisciplinary Research Networks:** Integration of materials science, chemical engineering, environmental science, and data science is evident in multidisciplinary teams working on Seshat's Composites.¹⁶⁹
- **Open Innovation Platforms:** Use of open-source platforms for data sharing, code development, and collaborative experimentation has facilitated global participation.^{167 170}
- **Educational and Outreach Initiatives:** Workshops, open-access publications, and community science projects engage students, early-career researchers, and the broader public.¹⁷¹

7.4 Challenges and Future Directions

- **Scalability and Standardization:** Scaling up HDCNS production and ensuring consistent quality are ongoing technical hurdles. Standardized protocols for material characterization and performance benchmarking are needed. ¹⁷²
- **Interfacial Engineering:** Achieving optimal dispersion and adhesion of HDCNS within diverse matrices requires further research. ¹⁶³
- **Integration with Digital and AI Tools:** The use of machine learning and materials informatics to accelerate composite design and optimization is a promising but underdeveloped area. ^{173 174}
- **Regulatory and Market Acceptance:** Demonstrating compliance with building codes, automotive standards, and other regulatory frameworks is essential for market penetration.

8. Conclusion

Seshat's Composites stand at the forefront of sustainable materials innovation, offering a compelling blend of high performance, environmental responsibility, and open scientific collaboration. Defined by the integration of hemp-derived carbon nanosheets, hemp oil, and hemp lignin—the “Hemp Triforce”—these composites are engineered to deliver superior mechanical, thermal, and electrical properties while maintaining a strong commitment to sustainability and ecological harmony. The theoretical framework underpinning Seshat's Composites is robust, integrating established principles of composite science with novel insights from nanotechnology and green chemistry. The hypotheses guiding their development are clear, testable, and grounded in both empirical evidence and theoretical modeling.

The production of Seshat's Composites is a multidisciplinary process that integrates sustainable raw material sourcing, advanced

chemical and mechanical processing, and state-of-the-art composite manufacturing techniques. The performance and sustainability of these composites are highly sensitive to a range of production variables, including raw material selection, pretreatment methods, carbonization and activation conditions, matrix composition, manufacturing process, and integration of nanomaterials. Systematic optimization of these variables is essential for achieving the desired balance of strength, toughness, thermal stability, and environmental impact.

Documented applications and case studies demonstrate the versatility and high performance of Seshat's Composites in civil engineering, transportation, aerospace, packaging, and consumer goods. Their performance characteristics—high strength-to-weight ratios, durability, thermal stability, biodegradability, and customizability—are validated through a combination of real-world demonstrators, experimental studies, and collaborative innovation projects. The integration of intelligent, multifunctional capabilities further distinguishes Seshat's Composites as a forward-looking solution for the challenges of modern engineering and sustainability.

Ongoing research, open-source data initiatives, and industry partnerships continue to drive the evolution of Seshat's Composites, ensuring that their development is informed by rigorous testing, life cycle assessment, and real-world feedback. As research continues to address challenges in scalability, standardization, and integration with digital tools, Seshat's Composites are poised to play a transformative role in the future of advanced materials and sustainable development.

References


1. **#36 - How To Make a Natural Composite**. Surjan Singh. December 14, 2020. <https://surjan.substack.com>
2. **(PDF) EXPERIMENTAL STUDIES ON MECHANICAL PROPERTIES OF POLYMER BASED COMPOSITES**. Satish Geeri; PRASAD S. SAMBHU; V.V.S. Prasad. January 01, 2018. <https://www.researchgate.net>
3. **(PDF) Hemp Fibres: Essentials, Composites or Nanocomposites and Technical Applications**. Ayesha Kausar; Ishaq Ahmad. November 17, 2023. <https://www.researchgate.net>
4. **(PDF) New Technologies for Hemp Based Advanced Composites**. Rainer Nowotny et al. March 01, 2016. <https://www.researchgate.net>
5. **(PDF) Sustainable hemp-based composites for the building industry application**. Ivana Schwarzova et al. July 21, 2017. <https://www.researchgate.net>
6. **10. Open Source Hardware - From Fibers to Fabric**. Marion Banon. April 06, 2023. <https://class.textile-academy.org>
7. **A Comprehensive Framework and Call for Collaborative Validation: Hemp-Derived Carbon Nanosheets (HDCNS), HDCNS-Composites, 100% Organic "Diamond Composites" made from 100% Hemp (HDCNS, Hemp Oil and Hemp Lignin), and Potential Applications | PDF | Composite Material | Graphene**. <https://www.scribd.com>
8. **Advancement in hemp fibre polymer composites: a comprehensive review**. Gauri S. Deshmukh. August 01, 2022. <https://www.degruyter.com>
9. **An Open-Source ABAQUS Plug-In for Delamination Analysis of 3D Printed Composites**. Efstratios Polyzos et al. May 02, 2023. <https://www.mdpi.com>
10. **Analysis of Composite Structures in Curing Process for Shape Deformations and Shear Stress: Basis for Advanced Optimization**. <https://www.mdpi.com>
11. **CAPE Laboratory**. sdsmt.edu. <https://www.sdsmt.edu>
12. **Carbon nanosheets**. patents.google.com. May 05, 2014. <https://patents.google.com>
13. **Case Studies**. compositesuk.co.uk. May 15, 2025. <https://compositesuk.co.uk>
14. **Collab Composite: Global Innovation Hub**. Arctic Business. March 26, 2025. <https://abi.se>
15. **Composite material - Wikipedia**. May 12, 2025. <https://en.wikipedia.org>
16. **Composite materials at a glance**. Royal Society. February 21, 2023. <https://www.rsc.org>
17. **Composites manufacturing - A215**. compositeskn.org. March 10, 2021. <https://compositeskn.org>
18. **Custom Composite Manufacturing - Fabrication & Products | ACP Composites**. ACP Composites. July 28, 2023. [url@hyphttps://acpcomposites.com](https://acpcomposites.com)
19. **Definitive Review of Nanobiochar | ACS Omega**. <https://pubs.acs.org>
20. **Development of Sustainable Composite Materials | FP7 | CORDIS ! European Commission**. CORDIS, cordis.europa.eu. February 10, 2022. <https://cordis.europa.eu>
21. **Diamond Open Access**. Science Europe. <https://scienceeurope.org>
22. **Effect of Diamond Phase Dispersion on the Properties of Diamond-SiC-Si Composites**. Sergey P Bogdanov et al. July 28, 2023. <https://www.mdpi.com>
23. **Effect of extraction methods on the molecular structure and thermal stability of kenaf (Hibiscus cannabinus core) biomass as an alternative bio-filler for rubber composites -**

- PubMed.** <https://pubmed.ncbi.nlm.nih.gov>
24. **Effects of chemical-physical pre-treatment processes on hemp fibres for reinforcement of composites and for textiles - ScienceDirect.** <https://www.sciencedirect.com>
 25. **Effects of nanoparticles on tensile, electrical, and thermal properties of Hemp/PBTG composites | Fibers and Polymers.** <https://link.springer.com>
 26. **Efficient and environmentally friendly techniques for extracting lignin from lignocellulose biomass and subsequent uses: A review - ScienceDirect.** <https://www.sciencedirect.com>
 27. **Energy-Storing Nanomaterial Made From Hemp.** Katherine Bourzac. March 27, 2023. <https://cen.acs.org>
 28. **Engineering and evaluation of hemp fibre reinforced polypropylene composites: Fibre treatment and matrix modification - ScienceDirect.** <https://www.sciencedirect.com>
 29. **Experimental Study on Compressive and Flexural Performance of Lightweight Cement-Based Composites Reinforced with Hybrid Short Fibers.** Cong-Thuat Dang et al. June 19, 2023. <https://www.mdpi.com>
 30. **Experimental investigation of hemp fiber hybrid composite material for automotive application - ScienceDirect.** <https://www.sciencedirect.com>
 31. **Experimental investigation on fatigue life and tensile strength of carbon fiber-reinforced PLA composites based on fused deposition modeling - Scientific Reports.** Kargar et al. October 24, 2023. <https://www.nature.com>
 32. **Extraction of cellulose fibers from flax and hemp: a review | Cellulose.** <https://link.springer.com>
 33. **Extraction strategies for lignin, cellulose, and hemicellulose to obtain valuable products from biomass | Advanced Composites and Hybrid Materials.** <https://link.springer.com>
 34. **Fabrication Processes of Composite Materials.** Masrath Sultana. June 04, 2023. <https://masrath-sultana.medium.com>
 35. **Fabrication of carbon-based nanocomposite films by spin-coating process: An experimental and modeling study of the film thickness - ScienceDirect.** <https://www.sciencedirect.com>
 36. **Frontiers | Impact of biochar on the fungal decay resistance of hemp-polylactic acid composites against wood basidiomycetes.** Mariem Zouari; Marica Mikuljan; Matthew Schwarzkopf. February 27, 2023. <https://www.frontiersin.org>
 37. **GitHub - MaterialInformatics/MaterialsInformatics: MaterialsInformatics is a Python package that provides direct, easy-to-use black-box solutions for materials informatics applications, especially ones based on imaging data that emerge in materials science.** MaterialInformatics. November 24, 2022. <https://github.com>
 38. **GitHub - marielandryceo/hdcns-composites: Hemp-derived Carbon Nanosheets integrated Into Various Matrixes for Composite Materials.** Marielandryceo. March 25, 2025. <https://github.com>
 39. **GitHub - ranamihir/btp: Data Driven Modelling of Composites.** Ranamihir. August 31, 2016. <https://github.com>
 40. **Hemp Carbon Makes Supercapacitors Superfast.** Asmedotorg. July 31, 2013. <https://www.asme.org>
 41. **Hemp Derived Carbon Nanosheets Better Than Graphene.** Aaron Jackson. August 29, 2014.

<https://www.intelligentliving.co>

42. **Hemp Fibre Properties and Processing Target Textile: A Review - PMC.**
<https://pmc.ncbi.nlm.nih.gov>
43. **Hemp Oil Extraction: Methods and Process for Quality Hemp Extract Oils.** Raquel Gonzalez. February 19, 2025. <https://www.rootsciences.com>
44. **Hemp-derived carbon nanosheets help build cheap, high-performance supercapacitors.** Dario Borghino. August 20, 2014. <https://newatlas.com>
45. **Industrial Hemp Fibers: An Overview.** <https://www.mdpi.com>
46. **Influence of Lignin Type on the Properties of Hemp Fiber-Reinforced Polypropylene Composites.** <https://www.mdpi.com>
47. **Interconnected Carbon Nanosheets Derived from Hemp for Ultrafast Supercapacitors with High Energy | ACS Nano.** <https://pubs.acs.org>
48. **Interconnected carbon nanosheets derived from hemp for ultrafast supercapacitors with high energy - PubMed.** <https://pubmed.ncbi.nlm.nih.gov>
49. **Introducing HDCNS-Composites: Hemp-Derived Carbon Nanosheets Integrated Into Various Matrixes for Composite Materials : materials.** marielandry. March 25, 2025. <https://www.reddit.com>
50. **Introduction to Composite Materials | IntechOpen.** www.intechopen.com. <https://www.intechopen.com>
51. **Introduction to Composite Materials.** [addcomposites.com](https://www.addcomposites.com). September 27, 2024. <https://www.addcomposites.com>
52. **Introductory Chapter: Background on Composite Materials | IntechOpen.** <https://www.intechopen.com>
53. **Marie Seshat Landry - Resume - February 14, 2025 | PDF | Artificial Intelligence | Intelligence (AI) & Semantics.** <https://www.scribd.com>
54. **Marie Seshat Landry: A Visionary Leader in Innovation and Sustainability.** Marie Seshat Landry. August 12, 2024. <https://www.marielandryceo.com>
55. **Mechanical Testing of Composites.** [addcomposites.com](https://www.addcomposites.com). October 08, 2024. <https://www.addcomposites.com>
56. **Modification of hemp fibers (Cannabis Sativa L.) for composite applications - ScienceDirect.** <https://www.sciencedirect.com>
57. **Natural Fibers in Composite Materials for Sustainable Building: A State-of-the-Art Review on Treated Hemp Fibers and Hurds in Mortars.** <https://www.mdpi.com>
58. **News & Events.** [nextcomp.ac.uk](https://www.nextcomp.ac.uk). <https://www.nextcomp.ac.uk>
59. **Novel sustainable hemp-based composites for application in the building industry: Physical, thermal and mechanical characterization - ScienceDirect.** <https://www.sciencedirect.com>
60. **Open manufacturing - Wikipedia.** <https://en.wikipedia.org>
61. **Optimization of hempseed oil extraction by n-hexane - ScienceDirect.** <https://www.sciencedirect.com>
62. **Optimizing Hemp Fiber Production for High Performance Composite Applications - PMC.** <https://pmc.ncbi.nlm.nih.gov>
63. **Polymers | Free Full-Text | Multi-Objective Optimization of Curing Profile for Autoclave**

- Processed Composites: Simultaneous Control of Curing Time and Process-Induced Defects.** <https://www.mdpi.com>
64. **RETRACTED ARTICLE: Enhanced tensile strength and thermal conductivity in copper diamond composites with B4C coating - Scientific Reports.** Sun et al. September 06, 2017. <https://www.nature.com>
65. **Recent developments and future perspectives of biorenewable nanocomposites for advanced applications.** Austine Ofondu Chinomso Iroegbu; Suprakas Sinha Ray. January 01, 2022. <https://www.degruyterbrill.com>
66. **Recent developments in the synthesis of composite materials for aerospace: case study.** Material Science & Engineering International Journal. October 08, 2024. <https://medcraveonline.com>
67. **Research Topics.** composites.syr.edu. <http://composites.syr.edu>
68. **Seshat Data.** seshat-db.com. <https://seshat-db.com>
69. **Seshat: Global History Databank.** Seshat 0.1.0 documentation. <https://seshat-global-history-databank.github.io>
70. **Simonetta Boria - Scientific publications.** simonettaboria.it. <https://www.simonettaboria.it>
71. **Surface modification of activated hemp hurd carbon with Sn nanoparticles for enhanced supercapacitors performance - ScienceDirect.** <https://www.sciencedirect.com>
72. **Sustainable Raw Material Sourcing.** Purbasha Giri. May 05, 2024. <https://ruralhandmade.com>
73. **Targeted Pre-Treatment of Hemp Fibers and the Effect on Mechanical Properties of Polymer Composites.** <https://www.mdpi.com>
74. **The Direct 3D Printing of Functional PEEK/Hydroxyapatite Composites via a Fused Filament Fabrication Approach.** <https://www.mdpi.com>
75. **The Most Popular Composite Fabrication Methods.** SMITeam. October 20, 2019. <https://www.smicomposites.com>
76. **Use of lignin as a compatibiliser in hemp/epoxy composites - ScienceDirect.** <https://www.sciencedirect.com>
77. **Utilizing the Potential of Waste Hemp Reinforcement: Investigating Mechanical and Thermal Properties of Polypropylene and Polylactic Acid Biocomposites | ACS Omega.** <https://pubs.acs.org>
78. **hdcns-composites/Theoretical_Integration_and_Formulation_of_HDCNS_Composites_and_Diamond_Composites at main · marielandryceo/hdcns-composites.** <https://github.com>
79. **marielandryceo - Overview.** GitHub. <https://github.com>
80. **marielandryceo Publisher Publications - Issuu.** <https://issuu.com>



95e41e8a-fc03-43d5-afbc-1ccb6eb67a62