

Seshat's Composites: A Hemp-Based Revolution in Sustainable Advanced Materials

Marie Seshat Landry

Landry Industries – Organic Defense & Innovation

May 28, 2025

Abstract

Seshat's Composites represent a new class of biogenic materials engineered from hemp-derived carbon allotropes and hemp oil. This white paper introduces the scientific foundation, synthesis protocol, and potential applications of the composites in military, environmental, architectural, and off-world domains. A core objective is to replace petrochemical-based composite systems with regenerative, carbon-negative alternatives.

1 Introduction

The Organic Revolution of 2030 calls for sustainable, ethical alternatives to synthetic materials. Hemp—one of Earth's most versatile plants—can be transformed into a range of carbon allotropes with tunable physical and electrical properties. When blended with hemp oil as a binding medium, a scalable, biodegradable composite emerges, termed **Seshat's Composite (SC)**.

2 Core Formula

Seshat's Composites can be represented by the following symbolic formulation:

$$SC = H_o + \sum_{i=1}^n \alpha_i H_{c_i} \quad (1)$$

Where:

- SC = Final Seshat's Composite
- H_o = Hemp Oil (binder)

- H_{c_i} = Individual hemp carbon allotrope (biochar, amorphous, activated, graphitic, etc.)
- α_i = Proportionality constant representing weight % of each carbon allotrope
- n = Number of different carbon allotropes in the blend

This formulation is scalable and modular. Properties such as tensile strength, hardness, conductivity, and biodegradability can be tuned by adjusting α_i values and curing conditions.

3 Materials and Methods

3.1 Materials

- Industrial hemp stalks (*Cannabis sativa*)
- Cold-pressed hemp seed oil
- Laboratory kiln or pyrolysis reactor (400–1100°C)
- Hydraulic press
- Steel or ceramic molds

3.2 Synthesis Protocol

1. **Carbonization:** Hemp biomass is pyrolyzed to create multiple carbon allotropes.
2. **Classification:** Carbon fractions are sieved and sorted by morphology and density.
3. **Mixing:** Hemp oil and selected carbon allotropes are blended at a target ratio (e.g., 70:30 by weight).
4. **Molding and Curing:** The mixture is pressed into shape under pressure (10–50 MPa) and heat (80–180°C).
5. **Finishing:** Panels are post-cured and optionally laminated, doped, or embedded with electronics.

4 Properties and Performance

By tuning carbon content, Seshat’s Composites can exhibit:

- Tensile strength: 50–150 MPa (projected)
- Electrical conductivity: tunable from insulating to semiconductive
- Biodegradability: ~90% over 2–5 years (with no toxic residue)
- Density: 0.9–1.3 g/cm³

5 Applications

- **Defense:** Lightweight armor, drone exteriors, ballistic panels
- **Construction:** Panels, roofing, insulation, formwork
- **Space Tech:** Radiation shields, off-world habitats
- **Sustainable Electronics:** Bioresin-based PCBs, conductive films

6 Environmental Impact

Seshat's Composites are carbon-negative and petrochemical-free. Their life cycle enables:

- CO₂ sequestration during hemp cultivation
- Safe end-of-life composting or recycling
- Minimal industrial toxicity

7 Conclusion

Seshat's Composites signal a paradigm shift in advanced material design. By leveraging nature's most regenerative plant and a circular processing model, we can replace toxic composites with ethical, scalable materials suitable for Earth and beyond.

8 Future Work

- Ballistic certification under NATO STANAG 2920
- Conductivity tuning with dopants or ionic resins
- Integration with autonomous manufacturing platforms