

Seshat’s Dual-Lignin Architecture:

A Pre-Experimental Proposal for 100% Bio-Based Hemp Vitrimer Bionanocomposites
With Expanded Carbon Morphology Spectrum and FGE Reactive Diluent Pathway

Marie-Soleil Seshat Landry
Conceptual Design

Theoretical Framework

March 31, 2026

Abstract

This proposal presents a novel dual-batch modified lignin architecture for creating 100% bio-based vitrimer epoxy matrices derived from hempseed oil. The “Seshat Lignin” system combines maleinated lignin (carboxyl/aldehyde functionalities) and Mannich lignin (amine functionalities) with epoxidized hempseed oil to establish a self-catalyzing, dual-dynamic covalent network. This architecture enables both transesterification and imine exchange mechanisms without external catalysts. A key innovation is the compatibility with a **graded reinforcement spectrum** spanning from native hemp bast fiber to carbonized morphologies (biochar, activated carbon, carbonized hemp fiber, hemp graphene/nanosheets), all derived from hemp feedstock. The dual-lignin chemistry provides adaptive interface compatibility across hydrophilic to graphitic surfaces. Additionally, an advanced formulation pathway incorporating **furfuryl glycidyl ether (FGE)** as a reactive diluent and dynamic bond modulator is proposed to enhance processability and introduce thermoreversible Diels-Alder chemistry. This pre-experimental document outlines the theoretical framework, hypothesized reaction mechanisms, detailed protocols for laboratory validation, and expected outcomes for materials scientists and polymer chemists.

Keywords: vitrimer, hempseed oil, lignin modification, dual-dynamic network, bionanocomposite, hemp carbon, biochar, furfuryl glycidyl ether, reactive diluent, circular economy, Seshat lignin

1 Introduction and Theoretical Framework

1.1 The Imperative for 100% Bio-Based Vitrimers

Thermoset polymers constitute approximately 18% of global polymer production (>65 million tons annually), yet their permanent covalent networks render them inherently non-recyclable [1]. Current end-of-life management relies on landfilling, incineration, or mechanical grinding into low-value fillers, creating significant environmental burdens [1, 2]. Vitrimerization—the incorporation of dynamic covalent bonds into crosslinked networks—offers a pathway to reprocessability while maintaining thermoset mechanical integrity [1, 2].

Bio-based vitrimers derived from renewable feedstocks (plant oils, lignin, tannins) have emerged as sustainable alternatives, but most systems rely on external catalysts or petrochemical co-reactants [3, 4]. A fully integrated, 100% bio-based vitrimer matrix compatible with natural fiber reinforcement remains an unmet challenge critical to circular material design.

1.2 Hemp as a Model Feedstock: The Carbon Morphology Spectrum

Hemp (*Cannabis sativa* L.) provides an ideal model for 100% bio-based composites, offering not merely mechanical reinforcement but a **graded carbon morphology spectrum**:

Table 1: Hemp-Derived Reinforcement Morphology Spectrum

Morphology	Processing	Surface Chemistry	Target Application
Bast fiber	Retting, mechanical	Hydrophilic (-OH rich)	Structural composites
Hemp hurds	Grinding, sieving	Hydrophilic, porous	Construction, automotive
Biochar (400–650°C)	Pyrolysis	Hydrophobic, reduced polarity	Thermal management, EMI shielding
Activated carbon	KOH/NaOH activation	High surface area, microporous	Supercapacitors, filtration
Carbonized hemp fiber (CHF)	Pyrolysis 500°C+ inert	Hydrophobic, carbon-rich	Aerospace, structural
Hemp graphene/nanosheets	Chemical exfoliation	Graphitic, tunable defects	Electronics, sensors

Carbonization pathway: Hemp biomass undergoes pyrolysis at 400–800°C, progressively converting cellulose/lignin to aromatic carbon structures. At 400–650°C, amorphous biochar with residual polar groups dominates [13]. Above 500°C in inert atmosphere, ordered graphitic domains emerge in carbonized hemp fiber (CHF), offering mechanical properties approaching synthetic carbon fibers [5]. Chemical activation (KOH, NaOH) at 400–800°C creates activated carbon with superior electrochemical performance [5].

Recent work demonstrates hemp biochar at 10–20 wt% loading increases thermal conductivity by 10–17% in bioepoxy composites, with optimal pyrolysis temperature at 550°C for stiffness/thermal stability trade-offs [13, 14]. Hybrid systems (hemp fiber + cashew biochar) achieve 94% tensile strength increase and 32–63% water absorption reduction [14].

1.3 The FGE Innovation: Reactive Diluent as Dynamic Modulator

Furfuryl glycidyl ether (FGE) is a bio-based epoxy monomer derived from furfural (obtained from agricultural residues such as corncobs, sugarcane bagasse, and oat hulls). While established as a reactive diluent in conventional epoxy systems, its integration into lignin-based vitrimer architectures remains unexplored.

Table 2: FGE Properties and Established Performance

Property	Value/Effect	Reference
Viscosity	Very low (monofunctional epoxy)	[15]
Optimal loading	10–20 wt%	[15]
Mechanical enhancement	16% flexural/tensile strength increase at 10–15 wt%	[15]
Adhesion improvement	300% with DETA curing agent	[15]
Dilution efficiency	Superior to commercial Cardura E10P	[15]
Furan functionality	Thermoreversible Diels-Alder chemistry	[15]

Key insight: FGE’s furan ring provides not merely viscosity reduction but an additional **dynamic covalent pathway** via Diels-Alder/retro-Diels-Alder reactions, potentially enabling lower-temperature reprocessing and stress relaxation mechanisms distinct from transesterification or imine exchange.

1.4 Prior Art and the Innovation Gap

1.4.1 Established Components

Table 3: Demonstrated Technologies in Lignin-Oil Vitrimer Systems

Component	Status	Key References
Epoxidized plant oils	Established	[7, 6]
Carboxylated lignin fractions	Established	[7, 8]
Aminated lignin	Demonstrated	[9]
Maleinated lignin	Demonstrated	[10]
Tertiary amine catalysis	Established	[7, 8]
Hemp biochar in epoxy	Demonstrated	[13, 14]
Carbonized hemp fiber	Emerging	[5]
FGE as reactive diluent	Established	[15]

1.4.2 The Gap: Dual-Batch Lignin with FGE Integration

No prior work combines:

1. Maleinated lignin and Mannich lignin as co-hardener systems
2. FGE as reactive diluent in lignin-based vitrimers
3. Triple-dynamic networks (transesterification + imine + Diels-Alder)
4. Adaptive interface chemistry across hemp carbon morphologies

The Seshat architecture hypothesizes that distributed functionality across two lignin populations—augmented by FGE’s furan chemistry—enables catalyst-free, multi-dynamic network behavior compatible with the full hemp carbon morphology spectrum.

2 Hypothesis: Seshat’s Dual-Lignin Architecture

2.1 Core Hypothesis

The combination of maleinated lignin (Batch A) and Mannich lignin (Batch B) with epoxidized hempseed oil creates a self-catalyzing, dual-dynamic vitrimer network. Batch A provides carboxyl groups for transesterification-based vitrimer behavior and aldehyde groups for imine formation; Batch B provides primary/secondary amines for epoxy curing and tertiary amines for transesterification catalysis. The resulting network exhibits both transesterification and imine exchange mechanisms without external catalyst addition. The dual-lignin chemistry provides adaptive interface compatibility with the full hemp carbon morphology spectrum from hydrophilic bast fiber to graphitic hemp nanosheets.

2.2 Extended Hypothesis: FGE Reactive Diluent Pathway

Incorporation of furfuryl glycidyl ether (FGE) at 10–20 wt% as a reactive diluent reduces viscosity to enable high lignin loadings (up to 70 wt%) while introducing thermoreversible Diels-Alder chemistry as a tertiary dynamic mechanism. FGE’s furan ring participates in dynamic crosslinking via Diels-Alder/retro-Diels-Alder reactions, enabling lower-temperature reprocessing (80–120°C) distinct from transesterification (>120°C). The aromatic furan ring enhances compatibility with lignin phenolics and carbon reinforcements through π – π interactions.

2.3 Architectural Rationale

Table 4: Functional Distribution in Seshat’s Dual-Lignin System

Batch	Modification	Functional Groups	Role in Network
A	Maleinization (succinic/maleic anhydride)	Carboxyl ($-\text{COOH}$) Aldehyde ($-\text{CHO}$)	Transesterification sites Imine crosslinking with B
B	Mannich reaction (formaldehyde + amine)	Primary/secondary amine ($-\text{NH}_2$, $-\text{NH}-$) Tertiary amine ($-\text{N}<$)	Epoxy curing, imine form Transesterification catalys
FGE	Bio-based monomer	Furan ring + epoxy	Reactive diluent, DA cher

2.4 Adaptive Interface Chemistry

A critical innovation of the Seshat architecture is **interface compatibility across the carbon morphology spectrum**:

Table 5: Interface Mechanisms with Hemp Carbon Morphologies


Reinforcement	Surface Type	Seshat Interaction	Expected Effect
Bast fiber	Hydrophilic (OH)	(- Esterification with Batch A carboxyls; H-bonding	Strong interfacial adhesion, stress transfer
Hemp hurds	Porous, hydrophilic	hy- Mechanical interlocking + chemical bonding	Crack deflection, toughening
Biochar (550°C)	Hydrophobic, residual polar	Van der Waals + polar interactions with Batch B amines	Dispersion stability, thermal percolation
Activated carbon	Microporous, basic surface	Acid-base interactions; tertiary amine coordination	Enhanced wetting, capacitance
CHF	Hydrophobic, carbon-rich	π - π stacking with aromatic lignin/FGE furan; amine surface activation	High modulus transfer, UV stability
Hemp nanosheets	Graphitic, defect sites	Tertiary amine electron donation to graphitic domains; covalent at defect sites	Electrical percolation, barrier properties

Hypothesis extension: The Mannich lignin’s tertiary amine groups and FGE’s furan rings serve as *surface activators* for carbon materials. Tertiary amines improve dispersion through electron donation to graphitic domains, while furan rings provide π - π stacking interactions with aromatic carbon surfaces.

2.5 Triple-Dynamic Network Mechanisms (with FGE)

2.5.1 Stage 1: Epoxy-Amine Curing (Room Temperature to 80°C)


Primary and secondary amines from Batch B react with epoxide rings on EHSO and FGE:



FGE’s monofunctional epoxy terminates chain ends, creating dangling furan groups pending dynamic crosslinking.

2.5.2 Stage 2: Carboxyl-Epoxy Esterification (80–120°C)


Carboxyl groups from Batch A react with remaining epoxy groups:



This forms β -hydroxy ester linkages—the foundation of transesterification-based vitrimer behavior.

2.5.3 Stage 3: Imine Formation (Concurrent with Stage 2)

Aldehydes from Batch A condense with amines from Batch B:



This establishes the secondary dynamic network via reversible imine bonds.

2.5.4 Stage 4: Diels-Alder Crosslinking (Optional, 60–100°C)

Furan rings from FGE react with maleimide groups (if added) or potentially with lignin-derived maleimide analogs:



Note: For 100% bio-based formulation without petrochemical maleimide, FGE may participate in self-association or alternative thermoreversible interactions with lignin-derived quinone methides.

2.5.5 Stage 5: Dynamic Exchange (Temperature-Dependent)

Three exchange mechanisms operate at distinct temperature windows:

Table 6: Temperature-Dependent Dynamic Mechanisms in Seshat-FGE System

Mechanism	Temperature	Catalyst	Application
Diels-Alder/retro-DA	60–120°C	None	Low-temp reprocessing, self-healing
Imine metathesis	80–150°C	Tertiary amine (Batch B)	pH-responsive reprocessing
Transesterification	120–200°C	Tertiary amine (Batch B)	High-temp reprocessing, welding

2.6 Self-Catalysis and Processability

The tertiary amines incorporated during Mannich modification serve triple roles:

1. Catalyze transesterification exchange (proven mechanism in benzoxazine-lignin vitrimers [8])
2. Enhance imine formation kinetics (general base catalysis)
3. **Surface activation of carbon reinforcements** (electron donation to graphitic domains)

FGE provides:

1. **Viscosity reduction:** 10–20 wt% FGE reduces viscosity to enable high lignin loadings (up to 70 wt%) without solvent processing
2. **Network mobility:** Monofunctional epoxy creates chain ends that enhance segmental motion for exchange reactions
3. **Dynamic pathway:** Furan chemistry enables lower-temperature reprocessing distinct from transesterification

This eliminates the need for external metal catalysts (Zn, Sn, Al) and enables solvent-free processing.

3 Detailed Experimental Protocol

3.1 Materials and Reagents

Table 7: Required Materials for Seshat Vitrimer Synthesis

Material	Specification	Source/Grade
Hempseed oil	Cold-pressed, >80% PUFA	Food or technical grade
Kraft lignin	Low-sulfonate content, M_w 1000–3000 g/mol	Commercial or hemp hurds
Furfuryl glycidyl ether (FGE)	>95%, bio-based	Commercial (Pennakem, etc.)
Formic acid (85%)	ACS reagent	Epoxidation co-reactant
Hydrogen peroxide (30%)	ACS reagent	Epoxidation oxidant
Succinic anhydride	>99%	Maleinization agent
Maleic anhydride	>99%	Alternative maleinization agent
Formaldehyde (37% aq.)	ACS reagent	Mannich reagent
Diethylenetriamine (DETA)	>99%	Mannich amine component
Triethylenetetramine (TETA)	>99%	Alternative Mannich amine
Toluene	Anhydrous, >99.8%	Reaction solvent
Pyridine	ACS reagent	Acylation catalyst

3.2 Step 1: Epoxidized Hempseed Oil (EHSO) Synthesis

Protocol based on [6, 7]:

1. **Pre-treatment:** Degum hempseed oil via water-degumming (2.5% distilled water, 50°C, 10 min, 2000 rpm) followed by bleaching (2.5% bleaching clay, 100°C, 15 min) to remove phospholipids and pigments [6].
2. **In-situ peroxyacid formation:** In a jacketed reactor equipped with mechanical stirrer and dropping funnel, combine:
 - 100 g refined hempseed oil
 - 0.5 g Amberlite IR-120 (acidic ion exchange resin, catalyst)
 - 22 g formic acid (85%)
3. Cool to 40°C. Add 75 g hydrogen peroxide (30%) dropwise over 2 h while maintaining $T < 60^\circ\text{C}$.
4. After addition, hold at 60°C for 4 h with vigorous stirring.
5. Separate organic phase, wash with distilled water until neutral pH, dry over anhydrous Na_2SO_4 .

6. **Characterization target:** Epoxy oxygen content 4–7% (ASTM D1652), iodine value < 10 g I₂/100g oil.

3.3 Step 2: Batch A—Maleinated Lignin (ML)

Protocol based on [10, 7]:

1. Dissolve 10 g Kraft lignin in 100 mL anhydrous pyridine under nitrogen atmosphere at 80°C.
2. Add 15 g succinic anhydride (1.5:1 molar ratio to lignin hydroxyl groups, estimated).
3. Stir at 80°C for 6 h under nitrogen.
4. Precipitate into excess acidified water (pH 2, HCl), filter, wash with distilled water until neutral.
5. Dry under vacuum at 60°C for 24 h.
6. **Characterization:** FT-IR (ester carbonyl at 1730 cm⁻¹, carboxyl at 1707 cm⁻¹), acid number (mg KOH/g, target > 150).

3.4 Step 3: Batch B—Mannich Lignin (MNL)

Protocol based on [9, 8]:

1. Dissolve 10 g Kraft lignin in 100 mL ethanol/water (1:1 v/v) at 60°C.
2. Add 5 g diethylenetriamine (DETA), stir until homogeneous.
3. Add 8 g formaldehyde (37% aqueous) dropwise over 30 min.
4. Reflux at 80°C for 4 h.
5. Distill off solvents under reduced pressure; dry under vacuum at 60°C.
6. **Characterization:** Elemental analysis (increased N content, target > 5 wt%), FT-IR (C–N stretch at 1150–1250 cm⁻¹), ¹H NMR (methylene protons from Mannich bridge at 3.5–4.0 ppm).

3.5 Step 4: Vitrimer Formulation and Curing

3.5.1 Standard Formulation (without FGE)

Critical formulation parameters:

Table 8: Seshat Vitrimer Formulation Variables (Standard)

Parameter	Range	Rationale
EHSO (epoxy equiv.)	100 phr	Base resin
Batch A (ML)	20–40 phr	Carboxyl/aldehyde source
Batch B (MNL)	15–30 phr	Amine source, catalyst reservoir
Batch A:B ratio	1:1 to 2:1	Controls imine vs. ester crosslink density
Total lignin content	35–70 wt%	Maximizes bio-content [7]

Curing protocol:

1. Dissolve Batch A and Batch B in minimum THF (sufficient for solubilization, typically 20–30 wt% solids).
2. Add EHSO, mix vigorously for 10 min.
3. Degas under vacuum for 5 min to remove entrapped air and residual solvent.
4. Cast into silicone molds (preheated to 80°C).
5. **Cure schedule:**
 - Stage 1: 80°C for 2 h (amine-epoxy reaction)
 - Stage 2: 120°C for 4 h (carboxyl-epoxy esterification, imine formation)
 - Stage 3: Post-cure at 150°C for 2 h (network maturation)

3.5.2 Advanced Formulation with FGE

FGE-enhanced formulation:

Table 9: Seshat-FGE Vitrimer Formulation Variables

Parameter	Range	Rationale
EHSO (epoxy equiv.)	80–90 phr	Reduced to accommodate FGE
FGE	10–20 phr	Reactive diluent, dynamic modulator
Batch A (ML)	20–40 phr	Carboxyl/aldehyde source
Batch B (MNL)	15–30 phr	Amine source, catalyst reservoir
Total epoxy:amine ratio	1:0.8–1:1.2	Stoichiometric control

Key differences from standard formulation:

1. **Solvent-free processing:** FGE reduces viscosity sufficiently to eliminate THF solvent
2. **Lower temperature curing:** Initial cure at 60–80°C (FGE enhances reactivity)
3. **Staged reprocessing capability:**
 - 80–100°C: Diels-Alder exchange (if maleimide added or self-association occurs)
 - 120–150°C: Imine exchange
 - 160–200°C: Transesterification

Expected outcomes with FGE:

- Initial viscosity: <5000 mPa·s at 25°C (processable without solvent)
- Tensile strength: +16% vs. standard formulation (per [15])
- Flexural strength: +16% vs. standard formulation
- Lower reprocessing temperature: 80–120°C vs. 160–200°C

3.6 Step 5: Hemp Carbon Morphology Integration

3.6.1 Protocol A: Bast Fiber/Hurd Composites (Hydrophilic)

1. Prepare unidirectional or woven hemp fiber preforms (target fiber volume fraction 40–50%).
2. Apply Seshat vitrimer formulation (standard or FGE-enhanced) via vacuum-assisted resin infusion (VARI) or resin transfer molding (RTM) at 80°C.
3. Cure following Stage 1–3 schedule.
4. **Alternative:** Pre-impregnate fibers with vitrimer resin, lay-up and cure via hot-pressing (120°C, 0.5 MPa, 4 h).

3.6.2 Protocol B: Biochar Integration (Hydrophobic)

Based on [13, 14]:

1. **Biochar preparation:** Pyrolyze hemp hurds at 550°C (5°C/min, 2 h hold) under nitrogen flow.
2. Mill and sieve to 25–100 μm particle size (optimal for mechanical properties [13]).
3. **Surface activation (optional):** Treat with 3% HCl to remove ash, enhance surface area.
4. Disperse biochar (10–20 wt% of total composite) in Seshat-FGE formulation using:
 - Three-roll milling for high-load mixes (FGE enables solvent-free dispersion)
 - Ultrasonication (500 W, 30 min) if solvent processing preferred
5. Degas and cure per standard protocol.
6. **Expected outcome:** 10–17% thermal conductivity increase; 32–63% water absorption reduction [13, 14].

3.6.3 Protocol C: Carbonized Hemp Fiber (CHF) Composites

1. **CHF preparation:** Pyrolyze hemp fiber at 500–800°C (5°C/min, 1 h hold) under nitrogen or argon flow [5].
2. Surface treatment (optional): Low-temperature oxygen plasma (50 W, 5 min) to introduce polar groups without structural damage.
3. Impregnate with Seshat-FGE formulation at 60–80°C under vacuum (FGE’s low viscosity enhances fiber wetting).
4. Cure via hot-pressing (120°C, 1 MPa, 4 h) to achieve fiber volume fraction 50–60%.

3.6.4 Protocol D: Hemp Graphene/Nanosheets

1. **Exfoliation:** Treat hemp biochar with KOH (1:4 weight ratio) at 800°C (chemical activation) followed by acid washing [5].
2. Disperse in DMF via ultrasonication (1 h) to achieve few-layer graphene/nanosheets.
3. Mix with Seshat-FGE formulation (0.5–2 wt% loading to avoid agglomeration; FGE aids dispersion via π – π interactions).
4. Cast and cure per standard protocol.
5. **Expected outcome:** Electrical percolation at <1 wt%; enhanced barrier properties.

4 Characterization Protocol

4.1 Chemical Structure Confirmation

Table 10: Analytical Techniques and Expected Results

Technique	Target	Expected Evidence	Ref. Standard
FT-IR (ATR)	Functional groups	Ester (1730), imine (1640–1690), epoxy consumption (910 cm^{-1} ↓) FGE furan (1010, 740 cm^{-1})	[7] [15]
^1H NMR	Mannich bridge	3.5–4.0 ppm (methylene)	[9]
^{13}C NMR	Carbonyl environments	170–175 ppm (ester/acid)	[10]
DSC	Cure kinetics	Two exotherms (amine + ester stages) DA/retro-DA reversibility (60–120°C)	[8] [15]
TGA	Thermal stability	$T_{d,5\%} > 300^\circ\text{C}$	[7]
Rheology	Viscosity	$< 5000 \text{ mPa}\cdot\text{s}$ at 25°C (FGE formulations)	[15]

4.2 Vitrimer Behavior Verification

Critical experiments to validate hypothesis:

1. Stress relaxation analysis (DMA):

- Sample geometry: $30 \times 5 \times 1 \text{ mm}^3$
- 1% strain, variable temperature (80–200°C)
- Target: Multiple relaxation regimes corresponding to DA (80–120°C), imine (100–150°C), and transesterification ($> 120^\circ\text{C}$) exchange
- Calculate activation energy E_a for each mechanism

2. Reprocessing demonstration:

- Grind cured sample to powder ($< 500 \mu\text{m}$)
- Hot-press at 100°C (DA regime), 140°C (imine regime), and 180°C (transesterification regime)
- Target: $> 80\%$ retention of tensile strength after 3 reprocessing cycles at any temperature

3. Chemical recycling:

- Aminolysis: Immerse in ethylene diamine (10 wt% in ethanol), 100°C , 3 h
- Target: Network dissolution; recovered oligomers suitable for polyurethane polyol synthesis (as demonstrated in [5])

4. Self-healing:

- Scratch sample surface, heat to 100°C (FGE-DA) or 150°C (standard) for 30 min
- Optical microscopy to assess scratch closure; compare FGE vs. standard formulations

4.3 Morphology-Specific Characterization

Table 11: Target Properties by Reinforcement Morphology

Morphology	Loading	Key Test	Target Value	Standard
Bast fiber	40–50 vol%	Flexural strength	200–350 MPa	ASTM D790
Biochar	10–20 wt%	Thermal conductivity	0.50 W·m ⁻¹ ·K ⁻¹	ASTM E1461
		Water absorption	32–63% reduction	ASTM D570
CHF	50–60 vol%	Tensile modulus	15–25 GPa	ASTM D638
Hemp graphene	0.5–2 wt%	Electrical conductivity	10 ⁻² –10 ⁻⁴ S/cm	Four-point probe

5 Why 100% Hemp Vitrimer is Key to Sustainable Bionanocomposites

5.1 Circularity and End-of-Life

Traditional hemp fiber-reinforced epoxies face a fundamental contradiction: bio-based reinforcement in non-recyclable matrix. The Seshat architecture resolves this through:

1. **Matrix recyclability:** Triple-dynamic bonds (with FGE) enable reprocessing at multiple temperature windows without fiber degradation [1]
2. **Feedstock unity:** Single agricultural source (hemp) provides oil, fiber, lignin, and carbon morphologies, minimizing transportation and processing emissions
3. **Cascading value:** Post-consumer composites can be pyrolyzed to recover carbon morphologies (biochar → activated carbon → graphene) for higher-value applications
4. **End-of-life options:**
 - Mechanical reprocessing (3+ cycles, 80–200°C)
 - Chemical recycling to oligomeric polyols
 - Pyrolytic recovery of carbon reinforcements
 - Composting of degraded matrix (ultimate biodegradation)

5.2 Carbon Sequestration Potential

Hemp cultivation sequesters 8–15 tonnes CO₂/hectare [5]. Converting this to durable composites with recyclable matrices creates a carbon sink that persists through multiple material lifecycles. The carbon morphology spectrum enables:

- **Short-term storage:** Bast fiber composites (5–10 year lifespan)
- **Medium-term storage:** Biochar/CHF composites (10–20 years, reprocessable)
- **Long-term storage:** Activated carbon for energy storage (decades, recoverable)

5.3 Application-Specific Impact

Table 12: Seshat Architecture Application Mapping

Application	Morphology	Key Property	Sustainability Gain
Automotive panels	Biochar + bast fiber	Lightweight, thermal management	100% bio-based, recyclable, 10–17% thermal conductivity increase
Aerospace structures	CHF	High specific modulus	Reprocessible vs. non-recyclable carbon fiber epoxy
Electronics housings	Hemp graphene	EMI shielding, conductivity	Bio-based alternative to metal/synthetic carbon
Construction	Hemp hurds + biochar	Insulation, fire resistance	Carbon-negative building material
Energy storage	Activated carbon	Supercapacitor electrodes	Recyclable energy storage infrastructure
Adhesives/sealants	FGE-enhanced matrix	Low-temp reprocessability	Solvent-free application, self-healing

6 Risk Assessment and Alternative Pathways

6.1 Technical Risks

Table 13: Risk Factors and Mitigation Strategies

Risk	Likelihood	Mitigation
Phase separation (ML/MNL incompatibility)	Medium	Add compatibilizer (epoxidized lignin fraction); adjust solvent system; use sequential addition rather than pre-mixing
Insufficient catalytic activity	Low–Medium	Add external $\text{Zn}(\text{acac})_2$ (5 mol%) as backup [7]; verify tertiary amine content by titration
Premature gelation	Medium	Stage curing: room temperature pre-cure (4 h) before heating; reduce Batch B amine reactivity by using aromatic amines
FGE volatility during cure	Low	Cure under nitrogen blanket; use closed molds; reduce initial cure temperature to 60°C
Biochar agglomeration	Medium	Optimize particle size (25–100 μm [13]); use FGE to improve wetting via π – π interactions
CHF/matrix delamination	Low–Medium	Surface plasma treatment; increase Batch B content for hydrophobic interface compatibility
DA chemistry interference	Low	Verify furan retention post-cure by FT-IR; adjust cure temperature to preserve furan functionality

6.2 Alternative Architectures

Should the dual-batch approach prove incompatible:

1. **Single-batch sequential modification:** Maleinize lignin first, then Mannich-modify the same material (risk: cross-reactivity of carboxyls with amines)
2. **Hybrid catalyst system:** Use Batch B for amine curing + external Zn^{2+} for transesterification (sacrifices catalyst-free claim)
3. **Fractionated approach:** Separate low- M_w lignin (mobile catalyst carrier) from high- M_w lignin (structural component) before modification
4. **FGE-only dynamic pathway:** Use FGE as sole dynamic component (DA chemistry) with conventional epoxy curing (simpler but less robust)
5. **Morphology-specific formulations:** Optimize Batch A:B ratio for each reinforcement type (e.g., higher Batch B for CHF, higher Batch A for bast fiber)

7 Conclusion and Expected Impact

The Seshat Dual-Lignin Architecture represents a conceptual advance in bio-based vitrimer design, proposing that distributed functionality across two modified lignin populations—augmented by FGE’s reactive diluent and dynamic chemistry—can achieve catalyst-free, multi-dynamic network behavior compatible with the full hemp carbon morphology spectrum. If validated, this system would provide:

- The first 100% hemp-derived vitrimer matrix (oil + lignin) compatible with both hydrophilic and hydrophobic reinforcements
- The first integration of FGE into lignin-based vitrimers, enabling solvent-free processing and lower-temperature reprocessing
- A pathway to fully recyclable hemp fiber bionanocomposites spanning structural to functional applications
- A model for circular material design using distributed rather than concentrated molecular functionality
- A carbon sequestration strategy with multiple lifecycle pathways (mechanical, chemical, pyrolytic)

Success would establish a new paradigm for lignin utilization in thermosetting polymers, moving beyond filler applications to structural, dynamic networks with adaptive interface chemistry and tunable reprocessing windows. The pre-experimental framework provided here enables any qualified polymer chemistry laboratory to validate or refute the hypothesis through systematic experimentation.

Data Availability

This pre-experimental proposal contains no primary data. All protocols are derived from cited literature sources. Upon experimental validation, raw data will be deposited in Zenodo or equivalent repositories with DOI assignment.

Author Information

Corresponding Conceptual Framework: Marie-Soleil Seshat Landry

Affiliation: Independent Research, Conceptual Design

Date: March 31, 2026

Conflicts of Interest

The author declares no competing financial interests. This work is presented as open-access pre-experimental research for community validation.

References

- [1] Ge, D.; Celik, S.; Cetin, D.; et al. Recycling Thermoset Systems by Vitrimerization Using Solid-State Shear Extrusion—A Feasibility Study. *Macromol. Mater. Eng.* **2025**, early access.
- [2] Recent Advances in Vitrimers and Advanced Composites: Sustainable Synthesis, Reprocessing, Welding and Applications. *Front. Mater.* **2026**, Research Topic.
- [3] Akhlaghi, S.G.; Morsch, S.; Sadeghi, H.; et al. Next-Generation Sustainable Composites with Flax Fibre and Biobased Vitrimer Epoxy Polymer Matrix. *Polymers* **2025**, *17*, 1891.
- [4] Rana, S.; Kar, G.P.; Bhowmick, A.K. Bio-Vitrimers for Sustainable Circular Bio-Economy. *Polymers* **2022**, *14*, 4209.
- [5] Hemp Fiber and Its Bio-Composites: A Comprehensive Review. *Sustainable Materials* **2025**, Springer.
- [6] Effect of Degumming and Bleaching on the Yield and Quality of Hempseed Oil Epoxidation. NSF PAR **2024**, 10666778.
- [7] Wang, S.; Xie, Y.; Liu, J.; Yuan, T.; et al. Lignin Fractions as Epoxy Hardeners with Transesterification Ability for Fully Biobased Reprocessable Thermosets. *ACS Sustain. Chem. Eng.* **2023**, *11*, 11502–11511.
- [8] Chen, Y.; Chen, J.; Wan, J.; et al. Lignin-Based Benzoxazine Resin with Excellent Comprehensive Properties via Vitrimer Chemistry. *ACS Sustain. Chem. Eng.* **2025**, *13*, 2275–2286.
- [9] Zhou, Q.; Luo, Z.; Ge, X.; et al. Preparation and Characterization of Aminated Lignin. *Int. J. Biol. Macromol.* **2013**, *62*, 295–302.
- [10] Asadi, S.; Jonoobi, M.; Kasmani, J.E.; et al. Synthesis and Characterization of Maleinated Lignin. *J. Polym. Environ.* **2022**, *30*, 1234–1245.
- [11] Zhao, N.; Sun, Y.; Zhang, H.; et al. Reinforcement Mechanisms of Lignin Nanoparticles in Biodegradable Cellulosic Films. *Sustain. Mater. Technol.* **2025**, *41*, e01337.
- [12] Yang, W.; Ouyang, Y.; et al. Lignin Nanoparticles and Their Nanocomposites. *Nanomaterials* **2021**, *11*, 2417.
- [13] Zhu, Y.; et al. Biochar from Hemp Hurds as Reinforcement in Bioepoxy Composites. *Polymers* **2023**, *15*, 3894.
- [14] Biochar-Reinforced Hemp Fiber Composites: Mechanical and Moisture Barrier Properties. *Compos. Part B Eng.* **2024**.

- [15] Furfuryl Glycidyl Ether as Reactive Diluent and Toughening Agent in Epoxy Resins: A Review. *J. Polym. Res.* **2024**, *31*, 45.